PHILIPS

Lighting



GentleSpace – High-quality, efficient lighting engineered for excellence in tough environments

GentleSpace gen4

GentleSpace gen4 is the ultimate lighting solution for industrial settings and indoor sports facilities. It exceeds expectations by ensuring superior light quality, improving employee safety and productivity, and complying with all the relevant safety regulations. Engineered for longevity, GentleSpace gen4 reduces the frequency, hassle, and costs of maintenance, making it ideal for high-ceiling installations. Its energy-efficient design cuts operational expenses, offering maximum application efficiency and an attractive total cost of ownership (TCO). This product range offers a wide variety of optics, beam angles (from very narrow to wide), lumen packages, and connectivity options. With GentleSpace gen4 you can easily create a tailor-made lighting solution for every high-ceiling application. Its modern, flat design makes it easier to install, clean, and maintain. The single optical window design provides superior visual performance. A variety of mounting possibilities and connectors, like the pre-mounted IP65 connector, enable quick and easy installation. The robust design allows to withstand harsh conditions in all sorts of environments. You can choose between various cover materials, including specialized variants for extreme temperatures (XT), hazardous areas (ATEX 2/22), and sports applications.Additionally, GentleSpace gen4 offers advanced connectivity options. It’s ready to use in connected lighting systems like Interact. Reliable, high-efficiency lighting with smart connectivity – a bright choice for a better future.Embrace sustainability with GentleSpace gen4, the highbay lighting solution that complies with the principles of the circular economy by prioritizing durability and recyclability. The luminaire is serviceable, with all the information available at your fingertips via the Signify Service tag app. Whether you are looking

for a reliable “fit and forget” solution or one that can be adapted and controlled after installation, GentleSpace gen4 is the right choice for you.

Benefits

- Robust design, created to withstand harsh conditions in all sorts of environments
- Compact product architecture, resistant to high impact (IK08), water, and dust (IP65)
- Excellent light uniformity and low glare for optimized working conditions with improved safety and greater visual comfort
- Attractive total cost of ownership thanks to its high luminous efficacy (up to 189 lm/W), long lifetime (100,000 hours @L85), and optimized lighting plan that requires fewer luminaires per application
- Easy installation. Single-piece, lighter architecture (approximately 20% lighter than the previous generation) with multiple mounting options for flexible installation in various environments and conditions
- Interact Ready connectivity for smart lighting. Connect to the cloud and discover additional ways to save energy through optimized efficiency, motion sensing and daylight harvesting, as well as improved lighting management, productivity, and safety
- Engineered with sustainability in mind. Meets lighting for circularity criteria to help you achieve your sustainability goals

Features

- Exceptional performance with UltraEfficient (UE, 189 lm/W) and High-Efficiency (HE, 183 lm/W) versions
- Long service life of 100,000 hours at L85
- High water (IP65) and impact protection (IK08)
- Wide variety of optics (wide beam/medium beam/narrow beam/extra narrow beam/high-rack/asymmetrical)
- Special options for a broad range of applications: Extreme version (XT) up to 70°C, Safety Class I or II, swimming pool protected version (SWP), marine protection (MSP), VDE certified ball-proof (BP) option, ATEX 2/22 certified version. Tested against a broad list of chemical substances that may be present in industrial settings
- Detachable mounting system for easy installation, including various mounting options and connectors (IP65 pre-mounted connector, or fly-wire cable)
- Robust, die-cast aluminum housing with efficient thermal management and flat front and rear design for easy installation, cleaning, and maintenance
- Single LED module design for superior light quality
- Access to the Signify Service tag app with service and maintenance information

Application

- Manufacturing sites (from food and beverage to heavy industry)
- Warehouses and logistics centers
- Indoor sports facilities, swimming pools, and exhibition halls

GentleSpace gen4

Versions



GentleSpace gen4-large, suspension



GentleSpace gen4-large, suspension, Interact ready



GentleSpace gen4-small, bracket, Interact ready



GentleSpace gen4-large, wall-bracket




GentleSpace gen4-small, bracket



GentleSpace gen4-small, wall-bracket


Dimensional drawing

BY580X suspended



With Wieland connector on a cable or free cable finish, cable length is: 0.5m or 1m or 1.5m, or 2m


700s suspended



With Wieland connector on a cable or free cable finish, cable length is: 0.5m or 1m or 1.5m, or 2m


Dimensional drawing

BY581X suspended




With Wieland connector on a cable or free cable finish, cable length is: 0.5m or 1m or 1.5m. or 2m

BY580P, BY582P suspended




With Wieland connector on a cable or free cable finish, cable length is: 0.5m or 1m or 1.5m. or 2m

BY581P, BY583P Bracket




With Wieland connector on a cable or free cable finish, cable length is: 0.5m or 1m or 1.5m. or 2m

BY580P, BY582P Wallmounted bracket




With Wieland connector on a cable or free cable finish, cable length is: 0.5m or 1m or 1.5m. or 2m

BY580P, BY582P Bracket




With Wieland connector on a cable or free cable finish, cable length is: 0.5m or 1m or 1.5m. or 2m

BY581X Bracket




With Wieland connector on a cable or free cable finish, cable length is: 0.5m or 1m or 1.5m. or 2m

BY580X Bracket



With Wieland connector on a cable or free cable finish, cable length is: 0.5m or 1m or 1.5m. or 2m

BY581P, BY583P Wallmounted bracket




With Wieland connector on a cable or free cable finish, cable length is: 0.5m or 1m or 1.5m. or 2m

GentleSpace gen4


Dimensional drawing

700S Bracket




With Wieland connector on a cable or free cable finish, cable length is: 0.5m or 1m or 1.5m. or 2m

BY581P, BY583P suspended



With Wieland connector on a cable or free cable finish, cable length is: 0.5m or 1m or 1.5m. or 2m

Product details



GentleSpace gen4-large, suspension



GentleSpace gen4-small, suspension

General Information	
Driver included	Yes
Number of gear units	1 unit
Service tag	Yes
Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Mechanical and Housing	
Housing Color	Silver
Ingress protection code	IP65
Emergency Operation	
Central Emergency	No
Approval and Application	
CE mark	Yes
ENEC mark	ENEC mark
Flammability mark	For mounting on easily flammable surfaces
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%

Light Technical (1/2)

Order Code	Full Product Name	Beam angle of light source	Correlated Color Temperature (Nom)	Color rendering index (CRI)	Luminous Efficacy (rated) (Nom)
910505102953	BY581P 700S/840 DIA WB GC SI	-	4000 K	>80	167 lm/W
910505102954	BY581P 700S/840 DIA HE WB GC SI	-	4000 K	>80	177 lm/W
910505102955	BY581P 700S/840 DIA WB GC SI BR	-	4000 K	>80	167 lm/W
910505102956	BY581P 700S/840 DIA HE WB GC SI BR	-	4000 K	>80	177 lm/W
910505102865	BY581X 250S/840 SIA WB GC SI H4 BR	-	4000 K	>80	174 lm/W
910505102866	BY581X 250S/840 SIA HE WB GC SI H4 BR	-	4000 K	>80	184 lm/W
910505102858	BY581X 250S/840 SIA WB GC SI H4	-	4000 K	>80	174 lm/W
910505102859	BY581X 350S/840 SIA WB GC SI H4	-	4000 K	>80	167 lm/W
910505102862	BY581X 250S/840 SIA HE WB GC SI H4	-	4000 K	>80	184 lm/W
910505102863	BY581X 350S/840 SIA HE WB GC SI H4	-	4000 K	>80	177 lm/W
910505102868	BY581X 250S/840 SIA WB GC SI ELP3 H4	-	4000 K	>80	174 lm/W
910505102869	BY581X 250S/840 SIA WB GC SI ELW3 H4	-	4000 K	>80	174 lm/W
910505102870	BY581X 250S/840 SIA HE WB GC SI ELP3 H4	-	4000 K	>80	184 lm/W
910505102871	BY581X 250S/840 SIA HE WB GC SI ELW3 H4	-	4000 K	>80	184 lm/W

Order Code	Full Product Name	Beam angle of light source	Correlated Color Temperature (Nom)	Color rendering index (CRI)	Luminous Efficacy (rated) (Nom)
910505102864	BY580X 170S/840 SIA WB GC SI H4 BR	-	4000 K	>80	167 lm/W
910505102867	BY580X 170S/840 SIA HE WB GC SI H4 BR	-	4000 K	>80	175 lm/W
910505104565	BY581P 250S/840 DIA HEWBGCSICHEMMBW1mCW5	-	4000 K	>80	181 lm/W
910505102872	BY580P 170S/840 PSU WB GC SI	-	4000 K	>80	167 lm/W
910505102874	BY580P 170S/840 PSU HE WB GC SI	-	4000 K	>80	175 lm/W
910505102876	BY580P 100S/840 DIA UE WB GC SI	-	4000 K	>80	182 lm/W
910505102878	BY580P 130S/840 DIA WB GC SI	-	4000 K	>80	171 lm/W
910505102879	BY580P 170S/840 DIA WB GC SI	-	4000 K	>80	167 lm/W
910505102882	BY580P 130S/840 DIA HE WB GC SI	-	4000 K	>80	178 lm/W
910505102883	BY580P 170S/840 DIA HE WB GC SI	-	4000 K	>80	175 lm/W
910505102886	BY580P 170S/840 DIA WB PC SI	-	4000 K	>80	155 lm/W
910505102890	BY580P 170S/840 DIA HE WB PC SI	-	4000 K	>80	164 lm/W
910505102894	BY580P 170S/840 DIA WB GC SI ELP3	-	4000 K	>80	167 lm/W
910505102896	BY580P 170S/840 DIA HE WB GC SI ELP3	-	4000 K	>80	175 lm/W
910505102898	BY580P 130S/840 DIA MB GC SI	-	4000 K	>80	169 lm/W
910505102899	BY580P 170S/840 DIA MB GC SI	-	4000 K	>80	164 lm/W
910505102903	BY580P 130S/840 DIA HE MB GC SI	-	4000 K	>80	178 lm/W
910505102904	BY580P 170S/840 DIA HE MB GC SI	-	4000 K	>80	174 lm/W
910505102914	BY580P 170S/840 DIA NB GC SI	10 or 24 degree(s)	4000 K	>80	164 lm/W
910505102916	BY580P 170S/840 DIA HE NB GC SI	10 or 24 degree(s)	4000 K	>80	174 lm/W
910505102918	BY580P 170S/840 DIA XNB GC SI	-	4000 K	>80	164 lm/W
910505102920	BY580P 170S/840 DIA HE XNB GC SI	-	4000 K	>80	174 lm/W
910505102922	BY580P 170S/840 DIA HRO GC SI	-	4000 K	>80	164 lm/W
910505102924	BY580P 170S/840 DIA HE HRO GC SI	-	4000 K	>80	174 lm/W
910505102926	BY580P 170S/865 DIA WB GC SI	-	6500 K	>80	164 lm/W
910505102928	BY580P 170S/865 DIA HE WB GC SI	-	6500 K	>80	172 lm/W
910505102930	BY580P 170S/830 DIA WB GC SI	-	3000 K	>80	155 lm/W
910505102932	BY580P 170S/830 DIA HE WB GC SI	-	3000 K	>80	159 lm/W
910505102934	BY580P 170S/940 DIA WB GC SI	-	4000 K	>90	157 lm/W
910505104540	BY582P 170S/840 DIA HE WB GC SI 0.5m CW5	-	4000 K	>80	167 lm/W
910505104542	BY582P 170S/840 DIA HE WB GC SI 1m CW5	-	4000 K	>80	167 lm/W
910505104554	BY580P 170S/840 DIA WB GC SI BP 1m CW5	-	4000 K	>80	167 lm/W
910505104556	BY580P 170S/840 DIA HE WB GC SI BP 1mCW5	-	4000 K	>80	175 lm/W
910505104558	BY580X 170S/840 SIA WB GC SI IA9	-	4000 K	>80	167 lm/W
910505104560	BY580X 170S/840 SIA HE WB GC SI ELP3 IA9	-	4000 K	>80	175 lm/W
910505102910	BY580P 170S/840 DIA ASYM GC SI MBW	-	4000 K	>80	157 lm/W
910505102912	BY580P 170S/840 DIA HE ASYM GC SI MBW	-	4000 K	>80	170 lm/W

Order Code	Full Product Name	Beam angle of light source	Correlated Color Temperature (Nom)	Color rendering index (CRI)	Luminous Efficacy (rated) (Nom)
910505102889	BY581P 250S/840 DIA WB GC SI BR	-	4000 K	>80	174 lm/W
910505102893	BY581P 250S/840 DIA HE WB GC SI BR	-	4000 K	>80	181 lm/W
910505102907	BY581P 250S/840 DIA ASYM GC SI BR	-	4000 K	>80	165 lm/W
910505102909	BY581P 250S/840 DIA HE ASYM GC SI BR	-	4000 K	>80	176 lm/W
910505102911	BY581P 250S/840 DIA ASYM GC SI MBW	-	4000 K	>80	165 lm/W
910505102913	BY581P 250S/840 DIA HE ASYM GC SI MBW	-	4000 K	>80	176 lm/W
910505102938	BY581P 350S/840 DIA HE WB GC SI BR XT 1m	-	4000 K	>80	177 lm/W
910505104545	BY581P 250S/840 DIA WB GC SI SWP BR	-	4000 K	>80	174 lm/W
910505104547	BY581P 250S/840 DIA HE WB GC SI SWP BR	-	4000 K	>80	181 lm/W
910505104551	BY581P 250S/840 DIA HE WB GC SI MSP BR	-	4000 K	>80	181 lm/W
910505104553	BY581P 250S/840 PSD WB GC II SI BR	-	4000 K	>80	174 lm/W
910505104559	BY581X 250S/840 SIA WB GC SI IA9	-	4000 K	>80	174 lm/W
910505104561	BY581X 250S/840 SIA HE WB GC SI ELP3 IA9	-	4000 K	>80	181 lm/W
910505104563	BY581P 250S/840 DIA HE WBGCSICHEMBR1mCW5	-	4000 K	>80	174 lm/W
910505102888	BY580P 170S/840 DIA WB GC SI BR	-	4000 K	>80	167 lm/W
910505102892	BY580P 170S/840 DIA HE WB GC SI BR	-	4000 K	>80	175 lm/W
910505102908	BY580P 170S/840 DIA HE ASYM GC SI BR	-	4000 K	>80	170 lm/W
910505104544	BY580P 170S/840 DIA WB GC SI SWP BR	-	4000 K	>80	167 lm/W
910505104546	BY580P 170S/840 DIA HE WB GC SI SWP BR	-	4000 K	>80	175 lm/W
910505104550	BY580P 170S/840 DIA HE WB GC SI MSP BR	-	4000 K	>80	175 lm/W
910505104562	BY580P 170S/840 DIA HE WBGCSICHEMBR1mCW5	-	4000 K	>80	167 lm/W
910505104564	BY580P 170S/840 DIA HEWBGCSICHEMMBW1mCW5	-	4000 K	>80	175 lm/W
910505102873	BY581P 250S/840 PSU WB GC SI	-	4000 K	>80	174 lm/W
910505102875	BY581P 250S/840 PSU HE WB GC SI	-	4000 K	>80	184 lm/W
910505102877	BY581P 200S/840 DIA UE WB GC SI	-	4000 K	>80	189 lm/W
910505102880	BY581P 250S/840 DIA WB GC SI	-	4000 K	>80	174 lm/W
910505102881	BY581P 350S/840 DIA WB GC SI	-	4000 K	>80	167 lm/W
910505102884	BY581P 250S/840 DIA HE WB GC SI	-	4000 K	>80	181 lm/W
910505102885	BY581P 350S/840 DIA HE WB GC SI	-	4000 K	>80	177 lm/W
910505102887	BY581P 250S/840 DIA WB PC SI	-	4000 K	>80	162 lm/W
910505102891	BY581P 250S/840 DIA HE WB PC SI	-	4000 K	>80	171 lm/W
910505102895	BY581P 250S/840 DIA WB GC SI ELD3	-	4000 K	>80	174 lm/W
910505102897	BY581P 250S/840 DIA HE WB GC SI ELD3	-	4000 K	>80	181 lm/W

Order Code	Full Product Name	Beam angle of light source	Correlated Color Temperature (Nom)	Color rendering index (CRI)	Luminous Efficacy (rated) (Nom)
910505102901	BY581P 250S/840 DIA MB GC SI	-	4000 K	>80	171 lm/W
910505102902	BY581P 350S/840 DIA MB GC SI	-	4000 K	>80	167 lm/W
910505102905	BY581P 250S/840 DIA HE MB GC SI	-	4000 K	>80	181 lm/W
910505102906	BY581P 350S/840 DIA HE MB GC SI	-	4000 K	>80	175 lm/W
910505102915	BY581P 250S/840 DIA NB GC SI	10 or 24 degree(s)	4000 K	>80	171 lm/W
910505102917	BY581P 250S/840 DIA HE NB GC SI	10 or 24 degree(s)	4000 K	>80	181 lm/W
910505102919	BY581P 250S/840 DIA XNB GC SI	-	4000 K	>80	171 lm/W
910505102921	BY581P 250S/840 DIA HE XNB GC SI	-	4000 K	>80	181 lm/W
910505102923	BY581P 250S/840 DIA HRO GC SI	-	4000 K	>80	171 lm/W
910505102925	BY581P 250S/840 DIA HE HRO GC SI	-	4000 K	>80	181 lm/W
910505102927	BY581P 250S/865 DIA WB GC SI	-	6500 K	>80	171 lm/W
910505102929	BY581P 250S/865 DIA HE WB GC SI	-	6500 K	>80	179 lm/W
910505102931	BY581P 250S/830 DIA WB GC SI	-	3000 K	>80	162 lm/W
910505102933	BY581P 250S/830 DIA HE WB GC SI	-	3000 K	>80	171 lm/W
910505102935	BY581P 250S/940 DIA WB GC SI	-	4000 K	>90	165 lm/W
910505102936	BY581P 250S/840 DIA HE WB GC SI XT 1m	-	4000 K	>80	181 lm/W
910505102937	BY581P 350S/840 DIA HE WB GC SI XT 1m	-	4000 K	>80	177 lm/W
910505104541	BY583P 250S/840 DIA HE WB GC SI 0.5m CW5	-	4000 K	>80	174 lm/W
910505104543	BY583P 250S/840 DIA HE WB GC SI 1m CW5	-	4000 K	>80	174 lm/W
910505104552	BY581P 250S/840 PSD WB GC II SI	-	4000 K	>80	174 lm/W
910505104555	BY581P 250S/840 DIA WB GC SI BP 1m CW5	-	4000 K	>80	174 lm/W
910505104557	BY581P 250S/840 DIA HE WB GC SI BP 1mCW5	-	4000 K	>80	181 lm/W
910505102856	BY580X 130S/840 SIA WB GC SI H4	-	4000 K	>80	171 lm/W
910505102857	BY580X 170S/840 SIA WB GC SI H4	-	4000 K	>80	167 lm/W
910505102860	BY580X 130S/840 SIA HE WB GC SI H4	-	4000 K	>80	178 lm/W
910505102861	BY580X 170S/840 SIA HE WB GC SI H4	-	4000 K	>80	175 lm/W

Light Technical (2/2)

Order Code	Full Product Name	Luminous Flux	Optic type
910505102953	BY581P 700S/840 DIA WB GC SI	70,000 lm	Wide beam
910505102954	BY581P 700S/840 DIA HE WB GC SI	70,000 lm	Wide beam
910505102955	BY581P 700S/840 DIA WB GC SI BR	70,000 lm	Wide beam
910505102956	BY581P 700S/840 DIA HE WB GC SI BR	70,000 lm	Wide beam
910505102865	BY581X 250S/840 SIA WB GC SI H4 BR	25,000 lm	Wide beam
910505102866	BY581X 250S/840 SIA HE WB GC SI H4 BR	25,000 lm	Wide beam
910505102858	BY581X 250S/840 SIA WB GC SI H4	25,000 lm	Wide beam
910505102859	BY581X 350S/840 SIA WB GC SI H4	35,000 lm	Wide beam
910505102862	BY581X 250S/840 SIA HE WB GC SI H4	25,000 lm	Wide beam

Order Code	Full Product Name	Luminous Flux	Optic type
910505102863	BY581X 350S/840 SIA HE WB GC SI H4	35,000 lm	Wide beam
910505102868	BY581X 250S/840 SIA WB GC SI ELP3 H4	25,000 lm	Wide beam
910505102869	BY581X 250S/840 SIA WB GC SI ELW3 H4	25,000 lm	Wide beam
910505102870	BY581X 250S/840 SIA HE WB GC SI ELP3 H4	25,000 lm	Wide beam
910505102871	BY581X 250S/840 SIA HE WB GC SI ELW3 H4	25,000 lm	Wide beam
910505102864	BY580X 170S/840 SIA WB GC SI H4 BR	17,000 lm	Wide beam

Order Code	Full Product Name	Luminous Flux	Optic type
910505102867	BY580X 170S/840 SIA HE WB GC SI H4 BR	17,000 lm	Wide beam
910505104565	BY581P 250S/840 DIA HEWBGCSICHEMMBW1mCW5	25,000 lm	Wide beam
910505102872	BY580P 170S/840 PSU WB GC SI	17,000 lm	Wide beam
910505102874	BY580P 170S/840 PSU HE WB GC SI	17,000 lm	Wide beam
910505102876	BY580P 100S/840 DIA UE WB GC SI	10,000 lm	Wide beam
910505102878	BY580P 130S/840 DIA WB GC SI	13,000 lm	Wide beam
910505102879	BY580P 170S/840 DIA WB GC SI	17,000 lm	Wide beam
910505102882	BY580P 130S/840 DIA HE WB GC SI	13,000 lm	Wide beam
910505102883	BY580P 170S/840 DIA HE WB GC SI	17,000 lm	Wide beam
910505102886	BY580P 170S/840 DIA WB PC SI	17,000 lm	Wide beam
910505102890	BY580P 170S/840 DIA HE WB PC SI	17,000 lm	Wide beam
910505102894	BY580P 170S/840 DIA WB GC SI ELP3	17,000 lm	Wide beam
910505102896	BY580P 170S/840 DIA HE WB GC SI ELP3	17,000 lm	Wide beam
910505102898	BY580P 130S/840 DIA MB GC SI	13,000 lm	Medium beam
910505102899	BY580P 170S/840 DIA MB GC SI	17,000 lm	Medium beam
910505102903	BY580P 130S/840 DIA HE MB GC SI	13,000 lm	Medium beam
910505102904	BY580P 170S/840 DIA HE MB GC SI	17,000 lm	Medium beam
910505102914	BY580P 170S/840 DIA NB GC SI	17,000 lm	Narrow beam
910505102916	BY580P 170S/840 DIA HE NB GC SI	17,000 lm	Narrow beam
910505102918	BY580P 170S/840 DIA XNB GC SI	17,000 lm	Narrow beam
910505102920	BY580P 170S/840 DIA HE XNB GC SI	17,000 lm	Narrow beam
910505102922	BY580P 170S/840 DIA HRO GC SI	17,000 lm	High-rack optic
910505102924	BY580P 170S/840 DIA HE HRO GC SI	17,000 lm	High-rack optic
910505102926	BY580P 170S/865 DIA WB GC SI	17,000 lm	Wide beam
910505102928	BY580P 170S/865 DIA HE WB GC SI	17,000 lm	Wide beam
910505102930	BY580P 170S/830 DIA WB GC SI	17,000 lm	Wide beam
910505102932	BY580P 170S/830 DIA HE WB GC SI	17,000 lm	Wide beam
910505102934	BY580P 170S/940 DIA WB GC SI	17,000 lm	Wide beam
910505104540	BY582P 170S/840 DIA HE WB GC SI 0.5m CW5	17,000 lm	Wide beam
910505104542	BY582P 170S/840 DIA HE WB GC SI 1m CW5	17,000 lm	Wide beam
910505104554	BY580P 170S/840 DIA WB GC SI BP 1m CW5	17,000 lm	Wide beam
910505104556	BY580P 170S/840 DIA HE WB GC SI BP 1mCW5	17,000 lm	Wide beam
910505104558	BY580X 170S/840 SIA WB GC SI IA9	17,000 lm	Wide beam
910505104560	BY580X 170S/840 SIA HE WB GC SI ELP3 IA9	17,000 lm	Wide beam
910505102910	BY580P 170S/840 DIA ASYM GC SI MBW	17,000 lm	Assymetric Beam angle
910505102912	BY580P 170S/840 DIA HE ASYM GC SI MBW	17,000 lm	Assymetric Beam angle
910505102889	BY581P 250S/840 DIA WB GC SI BR	25,000 lm	Wide beam
910505102893	BY581P 250S/840 DIA HE WB GC SI BR	25,000 lm	Wide beam
910505102907	BY581P 250S/840 DIA ASYM GC SI BR	25,000 lm	Assymetric Beam angle
910505102909	BY581P 250S/840 DIA HE ASYM GC SI BR	25,000 lm	Assymetric Beam angle
910505102911	BY581P 250S/840 DIA ASYM GC SI MBW	25,000 lm	Assymetric Beam angle
910505102913	BY581P 250S/840 DIA HE ASYM GC SI MBW	25,000 lm	Assymetric Beam angle
910505102938	BY581P 350S/840 DIA HE WB GC SI BR XT 1m	35,000 lm	Wide beam
910505104545	BY581P 250S/840 DIA WB GC SI SWP BR	25,000 lm	Symmetrical
910505104547	BY581P 250S/840 DIA HE WB GC SI SWP BR	25,000 lm	Symmetrical
910505104551	BY581P 250S/840 DIA HE WB GC SI MSP BR	25,000 lm	Wide beam
910505104553	BY581P 250S/840 PSD WB GC II SI BR	25,000 lm	Wide beam
910505104559	BY581X 250S/840 SIA WB GC SI IA9	25,000 lm	Wide beam
910505104561	BY581X 250S/840 SIA HE WB GC SI ELP3 IA9	25,000 lm	Wide beam
910505104563	BY581P 250S/840 DIA HE WBGCSICHEMBR1mCW5	25,000 lm	Wide beam
910505102888	BY580P 170S/840 DIA WB GC SI BR	17,000 lm	Wide beam
910505102892	BY580P 170S/840 DIA HE WB GC SI BR	17,000 lm	Wide beam
910505102908	BY580P 170S/840 DIA HE ASYM GC SI BR	17,000 lm	Assymetric Beam angle
910505104544	BY580P 170S/840 DIA WB GC SI SWP BR	17,000 lm	Symmetrical
910505104546	BY580P 170S/840 DIA HE WB GC SI SWP BR	17,000 lm	Symmetrical
910505104550	BY580P 170S/840 DIA HE WB GC SI MSP BR	17,000 lm	Wide beam
910505104562	BY580P 170S/840 DIA HE WBGCSICHEMBR1mCW5	17,000 lm	Wide beam
910505104564	BY580P 170S/840 DIA HEWBGCSICHEMMBW1mCW5	17,000 lm	Wide beam
910505102873	BY581P 250S/840 PSU WB GC SI	25,000 lm	Wide beam
910505102875	BY581P 250S/840 PSU HE WB GC SI	25,000 lm	Wide beam
910505102877	BY581P 200S/840 DIA UE WB GC SI	20,000 lm	Wide beam
910505102880	BY581P 250S/840 DIA WB GC SI	25,000 lm	Wide beam
910505102881	BY581P 350S/840 DIA WB GC SI	35,000 lm	Wide beam
910505102884	BY581P 250S/840 DIA HE WB GC SI	25,000 lm	Wide beam
910505102885	BY581P 350S/840 DIA HE WB GC SI	35,000 lm	Wide beam
910505102887	BY581P 250S/840 DIA WB PC SI	25,000 lm	Wide beam
910505102891	BY581P 250S/840 DIA HE WB PC SI	25,000 lm	Wide beam
910505102895	BY581P 250S/840 DIA WB GC SI ELD3	25,000 lm	Wide beam
910505102897	BY581P 250S/840 DIA HE WB GC SI ELD3	25,000 lm	Wide beam
910505102901	BY581P 250S/840 DIA MB GC SI	25,000 lm	Medium beam
910505102902	BY581P 350S/840 DIA MB GC SI	35,000 lm	Medium beam
910505102905	BY581P 250S/840 DIA HE MB GC SI	25,000 lm	Medium beam
910505102906	BY581P 350S/840 DIA HE MB GC SI	35,000 lm	Medium beam
910505102915	BY581P 250S/840 DIA NB GC SI	25,000 lm	Narrow beam

Order Code	Full Product Name	Luminous Flux	Optic type
910505102917	BY581P 250S/840 DIA HE NB GC SI	25,000 lm	Narrow beam
910505102919	BY581P 250S/840 DIA XNB GC SI	25,000 lm	Narrow beam
910505102921	BY581P 250S/840 DIA HE XNB GC SI	25,000 lm	Narrow beam
910505102923	BY581P 250S/840 DIA HRO GC SI	25,000 lm	High-rack optic
910505102925	BY581P 250S/840 DIA HE HRO GC SI	25,000 lm	High-rack optic
910505102927	BY581P 250S/865 DIA WB GC SI	25,000 lm	Wide beam
910505102929	BY581P 250S/865 DIA HE WB GC SI	25,000 lm	Wide beam
910505102931	BY581P 250S/830 DIA WB GC SI	25,000 lm	Wide beam
910505102933	BY581P 250S/830 DIA HE WB GC SI	25,000 lm	Wide beam
910505102935	BY581P 250S/940 DIA WB GC SI	25,000 lm	Wide beam
910505102936	BY581P 250S/840 DIA HE WB GC SI XT 1m	25,000 lm	Wide beam
910505102937	BY581P 350S/840 DIA HE WB GC SI XT 1m	35,000 lm	Wide beam

Order Code	Full Product Name	Luminous Flux	Optic type
910505104541	BY583P 250S/840 DIA HE WB GC SI 0.5m CW5	25,000 lm	Wide beam
910505104543	BY583P 250S/840 DIA HE WB GC SI 1m CW5	25,000 lm	Wide beam
910505104552	BY581P 250S/840 PSD WB GC II SI	25,000 lm	Wide beam
910505104555	BY581P 250S/840 DIA WB GC SI BP 1m CW5	25,000 lm	Wide beam
910505104557	BY581P 250S/840 DIA HE WB GC SI BP 1mCW5	25,000 lm	Wide beam
910505102856	BY580X 130S/840 SIA WB GC SI H4	13,000 lm	Wide beam
910505102857	BY580X 170S/840 SIA WB GC SI H4	17,000 lm	Wide beam
910505102860	BY580X 130S/840 SIA HE WB GC SI H4	13,000 lm	Wide beam
910505102861	BY580X 170S/840 SIA HE WB GC SI H4	17,000 lm	Wide beam

Operating and Electrical

Order Code	Full Product Name	Protection class IEC	Power Consumption	Suitable for random switching
910505102953	BY581P 700S/840 DIA WB GC SI	Safety class I	420 W	No
910505102954	BY581P 700S/840 DIA HE WB GC SI	Safety class I	397 W	No
910505102955	BY581P 700S/840 DIA WB GC SI BR	Safety class I	420 W	No
910505102956	BY581P 700S/840 DIA HE WB GC SI BR	Safety class I	397 W	No
910505102865	BY581X 250S/840 SIA WB GC SI H4 BR	Safety class I	144 W	Yes (relates to presence/ movement detection and daylight harvesting)
910505102866	BY581X 250S/840 SIA HE WB GC SI H4 BR	Safety class I	136 W	Yes (relates to presence/ movement detection and daylight harvesting)
910505102858	BY581X 250S/840 SIA WB GC SI H4	Safety class I	144 W	Yes (relates to presence/ movement detection and daylight harvesting)
910505102859	BY581X 350S/840 SIA WB GC SI H4	Safety class I	210 W	Yes (relates to presence/ movement detection and daylight harvesting)
910505102862	BY581X 250S/840 SIA HE WB GC SI H4	Safety class I	136 W	Yes (relates to presence/ movement detection and daylight harvesting)
910505102863	BY581X 350S/840 SIA HE WB GC SI H4	Safety class I	198 W	Yes (relates to presence/ movement detection and daylight harvesting)

Order Code	Full Product Name	Protection class IEC	Power Consumption	Suitable for random switching
910505102868	BY581X 250S/840 SIA WB GC SI ELP3 H4	Safety class I	144 W	Yes (relates to presence/ movement detection and daylight harvesting)
910505102869	BY581X 250S/840 SIA WB GC SI ELW3 H4	Safety class I	144 W	Yes (relates to presence/ movement detection and daylight harvesting)
910505102870	BY581X 250S/840 SIA HE WB GC SI ELP3 H4	Safety class I	136 W	Yes (relates to presence/ movement detection and daylight harvesting)
910505102871	BY581X 250S/840 SIA HE WB GC SI ELW3 H4	Safety class I	136 W	Yes (relates to presence/ movement detection and daylight harvesting)
910505102864	BY580X 170S/840 SIA WB GC SI H4 BR	Safety class I	102 W	Yes (relates to presence/ movement detection and daylight harvesting)
910505102867	BY580X 170S/840 SIA HE WB GC SI H4 BR	Safety class I	97 W	Yes (relates to presence/ movement detection and daylight harvesting)
910505104565	BY581P 250S/840 DIA HEWBGCSICHEMMBW1mCW5	Safety class I	138 W	No
910505102872	BY580P 170S/840 PSU WB GC SI	Safety class I	102 W	No
910505102874	BY580P 170S/840 PSU HE WB GC SI	Safety class I	97 W	No
910505102876	BY580P 100S/840 DIA UE WB GC SI	Safety class I	55 W	No
910505102878	BY580P 130S/840 DIA WB GC SI	Safety class I	76 W	No
910505102879	BY580P 170S/840 DIA WB GC SI	Safety class I	102 W	No
910505102882	BY580P 130S/840 DIA HE WB GC SI	Safety class I	73 W	No
910505102883	BY580P 170S/840 DIA HE WB GC SI	Safety class I	97 W	No
910505102886	BY580P 170S/840 DIA WB PC SI	Safety class I	110 W	No
910505102890	BY580P 170S/840 DIA HE WB PC SI	Safety class I	104 W	No
910505102894	BY580P 170S/840 DIA WB GC SI ELP3	Safety class I	102 W	No
910505102896	BY580P 170S/840 DIA HE WB GC SI ELP3	Safety class I	97 W	No
910505102898	BY580P 130S/840 DIA MB GC SI	Safety class I	77 W	No
910505102899	BY580P 170S/840 DIA MB GC SI	Safety class I	104 W	No
910505102903	BY580P 130S/840 DIA HE MB GC SI	Safety class I	73 W	No
910505102904	BY580P 170S/840 DIA HE MB GC SI	Safety class I	98 W	No
910505102914	BY580P 170S/840 DIA NB GC SI	Safety class I	104 W	No
910505102916	BY580P 170S/840 DIA HE NB GC SI	Safety class I	98 W	No
910505102918	BY580P 170S/840 DIA XNB GC SI	Safety class I	104 W	No
910505102920	BY580P 170S/840 DIA HE XNB GC SI	Safety class I	98 W	No
910505102922	BY580P 170S/840 DIA HRO GC SI	Safety class I	104 W	No
910505102924	BY580P 170S/840 DIA HE HRO GC SI	Safety class I	98 W	No
910505102926	BY580P 170S/865 DIA WB GC SI	Safety class I	104 W	No
910505102928	BY580P 170S/865 DIA HE WB GC SI	Safety class I	99 W	No

Order Code	Full Product Name	Protection class IEC	Power Consumption	Suitable for random switching
910505102930	BY580P 170S/830 DIA WB GC SI	Safety class I	110 W	No
910505102932	BY580P 170S/830 DIA HE WB GC SI	Safety class I	104 W	No
910505102934	BY580P 170S/940 DIA WB GC SI	Safety class I	108 W	No
910505104540	BY582P 170S/840 DIA HE WB GC SI 0.5m CW5	Safety class I	102 W	No
910505104542	BY582P 170S/840 DIA HE WB GC SI 1m CW5	Safety class I	102 W	No
910505104554	BY580P 170S/840 DIA WB GC SI BP 1m CW5	Safety class I	102 W	No
910505104556	BY580P 170S/840 DIA HE WB GC SI BP 1mCW5	Safety class I	97 W	No
910505104558	BY580X 170S/840 SIA WB GC SI IA9	Safety class I	102 W	Yes (relates to presence/ movement detection and daylight harvesting)
910505104560	BY580X 170S/840 SIA HE WB GC SI ELP3 IA9	Safety class I	97 W	Yes (relates to presence/ movement detection and daylight harvesting)
910505102910	BY580P 170S/840 DIA ASYM GC SI MBW	Safety class I	108 W	No
910505102912	BY580P 170S/840 DIA HE ASYM GC SI MBW	Safety class I	100 W	No
910505102889	BY581P 250S/840 DIA WB GC SI BR	Safety class I	144 W	No
910505102893	BY581P 250S/840 DIA HE WB GC SI BR	Safety class I	138 W	No
910505102907	BY581P 250S/840 DIA ASYM GC SI BR	Safety class I	152 W	No
910505102909	BY581P 250S/840 DIA HE ASYM GC SI BR	Safety class I	142 W	No
910505102911	BY581P 250S/840 DIA ASYM GC SI MBW	Safety class I	152 W	No
910505102913	BY581P 250S/840 DIA HE ASYM GC SI MBW	Safety class I	142 W	No
910505102938	BY581P 350S/840 DIA HE WB GC SI BR XT 1m	Safety class I	198 W	No

Order Code	Full Product Name	Protection class IEC	Power Consumption	Suitable for random switching
910505104545	BY581P 250S/840 DIA WB GC SI SWP BR	Safety class I	144 W	No
910505104547	BY581P 250S/840 DIA HE WB GC SI SWP BR	Safety class I	138 W	No
910505104551	BY581P 250S/840 DIA HE WB GC SI MSP BR	Safety class I	138 W	No
910505104553	BY581P 250S/840 PSD WB GC II SI BR	Safety class II	144 W	No
910505104559	BY581X 250S/840 SIA WB GC SI IA9	Safety class I	144 W	Yes (relates to presence/ movement detection and daylight harvesting)
910505104561	BY581X 250S/840 SIA HE WB GC SI ELP3 IA9	Safety class I	138 W	Yes (relates to presence/ movement detection and daylight harvesting)
910505104563	BY581P 250S/840 DIA HE WBGCSICHEMBR1mCW5	Safety class I	144 W	No
910505102888	BY580P 170S/840 DIA WB GC SI BR	Safety class I	102 W	No
910505102892	BY580P 170S/840 DIA HE WB GC SI BR	Safety class I	97 W	No
910505102908	BY580P 170S/840 DIA HE ASYM GC SI BR	Safety class I	100 W	No
910505104544	BY580P 170S/840 DIA WB GC SI SWP BR	Safety class I	102 W	No
910505104546	BY580P 170S/840 DIA HE WB GC SI SWP BR	Safety class I	97 W	No
910505104550	BY580P 170S/840 DIA HE WB GC SI MSP BR	Safety class I	97 W	No
910505104562	BY580P 170S/840 DIA HE WBGCSICHEMBR1mCW5	Safety class I	102 W	No
910505104564	BY580P 170S/840 DIA HEWBGCSICHEMMBW1mCW5	Safety class I	97 W	No
910505102873	BY581P 250S/840 PSU WB GC SI	Safety class I	144 W	No
910505102875	BY581P 250S/840 PSU HE WB GC SI	Safety class I	136 W	No
910505102877	BY581P 200S/840 DIA UE WB GC SI	Safety class I	106 W	No

Order Code	Full Product Name	Protection class IEC	Power Consumption	Suitable for random switching
910505102880	BY581P 250S/840 DIA WB GC SI	Safety class I	144 W	No
910505102881	BY581P 350S/840 DIA WB GC SI	Safety class I	210 W	No
910505102884	BY581P 250S/840 DIA HE WB GC SI	Safety class I	138 W	No
910505102885	BY581P 350S/840 DIA HE WB GC SI	Safety class I	198 W	No
910505102887	BY581P 250S/840 DIA WB PC SI	Safety class I	154 W	No
910505102891	BY581P 250S/840 DIA HE WB PC SI	Safety class I	146 W	No
910505102895	BY581P 250S/840 DIA WB GC SI ELD3	Safety class I	144 W	No
910505102897	BY581P 250S/840 DIA HE WB GC SI ELD3	Safety class I	138 W	No
910505102901	BY581P 250S/840 DIA MB GC SI	Safety class I	146 W	No
910505102902	BY581P 350S/840 DIA MB GC SI	Safety class I	210 W	No
910505102905	BY581P 250S/840 DIA HE MB GC SI	Safety class I	138 W	No
910505102906	BY581P 350S/840 DIA HE MB GC SI	Safety class I	200 W	No
910505102915	BY581P 250S/840 DIA NB GC SI	Safety class I	146 W	No
910505102917	BY581P 250S/840 DIA HE NB GC SI	Safety class I	138 W	No
910505102919	BY581P 250S/840 DIA XNB GC SI	Safety class I	146 W	No
910505102921	BY581P 250S/840 DIA HE XNB GC SI	Safety class I	138 W	No
910505102923	BY581P 250S/840 DIA HRO GC SI	Safety class I	146 W	No
910505102925	BY581P 250S/840 DIA HE HRO GC SI	Safety class I	138 W	No
910505102927	BY581P 250S/865 DIA WB GC SI	Safety class I	146 W	No
910505102929	BY581P 250S/865 DIA HE WB GC SI	Safety class I	140 W	No
910505102931	BY581P 250S/830 DIA WB GC SI	Safety class I	154 W	No
910505102933	BY581P 250S/830 DIA HE WB GC SI	Safety class I	146 W	No
910505102935	BY581P 250S/940 DIA WB GC SI	Safety class I	152 W	No
910505102936	BY581P 250S/840 DIA HE WB GC SI XT 1m	Safety class I	138 W	No
910505102937	BY581P 350S/840 DIA HE WB GC SI XT 1m	Safety class I	198 W	No
910505104541	BY583P 250S/840 DIA HE WB GC SI 0.5m CW5	Safety class I	144 W	No
910505104543	BY583P 250S/840 DIA HE WB GC SI 1m CW5	Safety class I	144 W	No
910505104552	BY581P 250S/840 PSD WB GC II SI	Safety class II	144 W	No
910505104555	BY581P 250S/840 DIA WB GC SI BP 1m CW5	Safety class I	144 W	No
910505104557	BY581P 250S/840 DIA HE WB GC SI BP 1mCW5	Safety class I	138 W	No
910505102856	BY580X 130S/840 SIA WB GC SI H4	Safety class I	76 W	Yes (relates to presence/ movement detection and daylight harvesting)
910505102857	BY580X 170S/840 SIA WB GC SI H4	Safety class I	102 W	Yes (relates to presence/ movement detection and daylight harvesting)
910505102860	BY580X 130S/840 SIA HE WB GC SI H4	Safety class I	73 W	Yes (relates to presence/ movement detection and daylight harvesting)
910505102861	BY580X 170S/840 SIA HE WB GC SI H4	Safety class I	97 W	Yes (relates to presence/ movement detection and daylight harvesting)

Controls and Dimming

Order Code	Full Product Name	Dimmable	Embedded control	Maximum dim level
910505102953	BY581P 700S/840 DIA WB GC SI	Yes	-	10%
910505102954	BY581P 700S/840 DIA HE WB GC SI	Yes	-	10%
910505102955	BY581P 700S/840 DIA WB GC SI BR	Yes	-	10%
910505102956	BY581P 700S/840 DIA HE WB GC SI BR	Yes	-	10%
910505102865	BY581X 250S/840 SIA WB GC SI H4 BR	Yes	Sensor SNH (R) 210	-
910505102866	BY581X 250S/840 SIA HE WB GC SI H4 BR	Yes	Sensor SNH (R) 210	-
910505102858	BY581X 250S/840 SIA WB GC SI H4	Yes	Sensor SNH (R) 210	-
910505102859	BY581X 350S/840 SIA WB GC SI H4	Yes	Sensor SNH (R) 210	-
910505102862	BY581X 250S/840 SIA HE WB GC SI H4	Yes	Sensor SNH (R) 210	-
910505102863	BY581X 350S/840 SIA HE WB GC SI H4	Yes	Sensor SNH (R) 210	-
910505102868	BY581X 250S/840 SIA WB GC SI ELP3 H4	Yes	Sensor SNH (R) 210	-
910505102869	BY581X 250S/840 SIA WB GC SI ELW3 H4	Yes	Sensor SNH (R) 210	-
910505102870	BY581X 250S/840 SIA HE WB GC SI ELP3 H4	Yes	Sensor SNH (R) 210	-
910505102871	BY581X 250S/840 SIA HE WB GC SI ELW3 H4	Yes	Sensor SNH (R) 210	-
910505102864	BY580X 170S/840 SIA WB GC SI H4 BR	Yes	Sensor SNH (R) 210	-
910505102867	BY580X 170S/840 SIA HE WB GC SI H4 BR	Yes	Sensor SNH (R) 210	-
910505104565	BY581P 250S/840 DIA HEWBGCSICHEMMBW1mCW5	Yes	-	10%
910505102872	BY580P 170S/840 PSU WB GC SI	No	-	-
910505102874	BY580P 170S/840 PSU HE WB GC SI	No	-	-
910505102876	BY580P 100S/840 DIA UE WB GC SI	Yes	-	10%
910505102878	BY580P 130S/840 DIA WB GC SI	Yes	-	10%
910505102879	BY580P 170S/840 DIA WB GC SI	Yes	-	10%
910505102882	BY580P 130S/840 DIA HE WB GC SI	Yes	-	10%
910505102883	BY580P 170S/840 DIA HE WB GC SI	Yes	-	10%
910505102886	BY580P 170S/840 DIA WB PC SI	Yes	-	10%
910505102890	BY580P 170S/840 DIA HE WB PC SI	Yes	-	10%
910505102894	BY580P 170S/840 DIA WB GC SI ELP3	Yes	-	10%
910505102896	BY580P 170S/840 DIA HE WB GC SI ELP3	Yes	-	10%

Order Code	Full Product Name	Dimmable	Embedded control	Maximum dim level
910505102898	BY580P 130S/840 DIA MB GC SI	Yes	-	10%
910505102899	BY580P 170S/840 DIA MB GC SI	Yes	-	10%
910505102903	BY580P 130S/840 DIA HE MB GC SI	Yes	-	10%
910505102904	BY580P 170S/840 DIA HE MB GC SI	Yes	-	10%
910505102914	BY580P 170S/840 DIA NB GC SI	Yes	-	10%
910505102916	BY580P 170S/840 DIA HE NB GC SI	Yes	-	10%
910505102918	BY580P 170S/840 DIA XNB GC SI	Yes	-	10%
910505102920	BY580P 170S/840 DIA HE XNB GC SI	Yes	-	10%
910505102922	BY580P 170S/840 DIA HRO GC SI	Yes	-	10%
910505102924	BY580P 170S/840 DIA HE HRO GC SI	Yes	-	10%
910505102926	BY580P 170S/865 DIA WB GC SI	Yes	-	10%
910505102928	BY580P 170S/865 DIA HE WB GC SI	Yes	-	10%
910505102930	BY580P 170S/830 DIA WB GC SI	Yes	-	10%
910505102932	BY580P 170S/830 DIA HE WB GC SI	Yes	-	10%
910505102934	BY580P 170S/940 DIA WB GC SI	Yes	-	10%
910505104540	BY582P 170S/840 DIA HE WB GC SI 0.5m CW5	Yes	-	10%
910505104542	BY582P 170S/840 DIA HE WB GC SI 1m CW5	Yes	-	10%
910505104554	BY580P 170S/840 DIA WB GC SI BP 1m CW5	Yes	-	10%
910505104556	BY580P 170S/840 DIA HE WB GC SI BP 1mCW5	Yes	-	10%
910505104558	BY580X 170S/840 SIA WB GC SI IA9	Yes	Sensor SNH (R) 210	-
910505104560	BY580X 170S/840 SIA HE WB GC SI ELP3 IA9	Yes	Sensor SNH (R) 210	-
910505102910	BY580P 170S/840 DIA ASYM GC SI MBW	Yes	-	10%
910505102912	BY580P 170S/840 DIA HE ASYM GC SI MBW	Yes	-	10%
910505102889	BY581P 250S/840 DIA WB GC SI BR	Yes	-	10%
910505102893	BY581P 250S/840 DIA HE WB GC SI BR	Yes	-	10%
910505102907	BY581P 250S/840 DIA ASYM GC SI BR	Yes	-	10%
910505102909	BY581P 250S/840 DIA HE ASYM GC SI BR	Yes	-	10%
910505102911	BY581P 250S/840 DIA ASYM GC SI MBW	Yes	-	10%
910505102913	BY581P 250S/840 DIA HE ASYM GC SI MBW	Yes	-	10%

Order Code	Full Product Name	Dimmable	Embedded control	Maximum dim level
910505102938	BY581P 350S/840 DIA HE WB GC SI BR XT 1m	Yes	-	10%
910505104545	BY581P 250S/840 DIA WB GC SI SWP BR	Yes	-	10%
910505104547	BY581P 250S/840 DIA HE WB GC SI SWP BR	Yes	-	10%
910505104551	BY581P 250S/840 DIA HE WB GC SI MSP BR	Yes	-	10%
910505104553	BY581P 250S/840 PSD WB GC II SI BR	Yes	-	10%
910505104559	BY581X 250S/840 SIA WB GC SI IA9	Yes	Sensor SNH (R) 210	-
910505104561	BY581X 250S/840 SIA HE WB GC SI ELP3 IA9	Yes	Sensor SNH (R) 210	-
910505104563	BY581P 250S/840 DIA HE WBGCSICHEMBR1mCW5	Yes	-	10%
910505102888	BY580P 170S/840 DIA WB GC SI BR	Yes	-	10%
910505102892	BY580P 170S/840 DIA HE WB GC SI BR	Yes	-	10%
910505102908	BY580P 170S/840 DIA HE ASYM GC SI BR	Yes	-	10%
910505104544	BY580P 170S/840 DIA WB GC SI SWP BR	Yes	-	10%
910505104546	BY580P 170S/840 DIA HE WB GC SI SWP BR	Yes	-	10%
910505104550	BY580P 170S/840 DIA HE WB GC SI MSP BR	Yes	-	10%
910505104562	BY580P 170S/840 DIA HE WBGCSICHEMBR1mCW5	Yes	-	10%
910505104564	BY580P 170S/840 DIA HEWBGCSICHEMMBW1mCW5	Yes	-	10%
910505102873	BY581P 250S/840 PSU WB GC SI	No	-	-
910505102875	BY581P 250S/840 PSU HE WB GC SI	No	-	-
910505102877	BY581P 200S/840 DIA UE WB GC SI	Yes	-	10%
910505102880	BY581P 250S/840 DIA WB GC SI	Yes	-	10%
910505102881	BY581P 350S/840 DIA WB GC SI	Yes	-	10%
910505102884	BY581P 250S/840 DIA HE WB GC SI	Yes	-	10%
910505102885	BY581P 350S/840 DIA HE WB GC SI	Yes	-	10%
910505102887	BY581P 250S/840 DIA WB PC SI	Yes	-	10%
910505102891	BY581P 250S/840 DIA HE WB PC SI	Yes	-	10%
910505102895	BY581P 250S/840 DIA WB GC SI ELD3	Yes	-	10%
910505102897	BY581P 250S/840 DIA HE WB GC SI ELD3	Yes	-	10%
910505102901	BY581P 250S/840 DIA MB GC SI	Yes	-	10%
910505102902	BY581P 350S/840 DIA MB GC SI	Yes	-	10%
910505102905	BY581P 250S/840 DIA HE MB GC SI	Yes	-	10%
910505102906	BY581P 350S/840 DIA HE MB GC SI	Yes	-	10%
910505102915	BY581P 250S/840 DIA NB GC SI	Yes	-	10%
910505102917	BY581P 250S/840 DIA HE NB GC SI	Yes	-	10%
910505102919	BY581P 250S/840 DIA XNB GC SI	Yes	-	10%
910505102921	BY581P 250S/840 DIA HE XNB GC SI	Yes	-	10%
910505102923	BY581P 250S/840 DIA HRO GC SI	Yes	-	10%
910505102925	BY581P 250S/840 DIA HE HRO GC SI	Yes	-	10%
910505102927	BY581P 250S/865 DIA WB GC SI	Yes	-	10%
910505102929	BY581P 250S/865 DIA HE WB GC SI	Yes	-	10%
910505102931	BY581P 250S/830 DIA WB GC SI	Yes	-	10%
910505102933	BY581P 250S/830 DIA HE WB GC SI	Yes	-	10%
910505102935	BY581P 250S/940 DIA WB GC SI	Yes	-	10%
910505102936	BY581P 250S/840 DIA HE WB GC SI XT 1m	Yes	-	10%
910505102937	BY581P 350S/840 DIA HE WB GC SI XT 1m	Yes	-	10%
910505104541	BY583P 250S/840 DIA HE WB GC SI 0.5m CW5	Yes	-	10%
910505104543	BY583P 250S/840 DIA HE WB GC SI 1m CW5	Yes	-	10%
910505104552	BY581P 250S/840 PSD WB GC II SI	Yes	-	10%
910505104555	BY581P 250S/840 DIA WB GC SI BP 1m CW5	Yes	-	10%
910505104557	BY581P 250S/840 DIA HE WB GC SI BP 1mCW5	Yes	-	10%
910505102856	BY580X 130S/840 SIA WB GC SI H4	Yes	Sensor SNH (R) 210	-
910505102857	BY580X 170S/840 SIA WB GC SI H4	Yes	Sensor SNH (R) 210	-
910505102860	BY580X 130S/840 SIA HE WB GC SI H4	Yes	Sensor SNH (R) 210	-
910505102861	BY580X 170S/840 SIA HE WB GC SI H4	Yes	Sensor SNH (R) 210	-

Mechanical and Housing

Order Code	Full Product Name	Explosion hazard class	Mech. impact protection code	Impact resistance for specific applications
910505102953	BY581P 700S/840 DIA WB GC SI	-	IK07	-
910505102954	BY581P 700S/840 DIA HE WB GC SI	-	IK07	-
910505102955	BY581P 700S/840 DIA WB GC SI BR	-	IK07	-
910505102956	BY581P 700S/840 DIA HE WB GC SI BR	-	IK07	-
910505102865	BY581X 250S/840 SIA WB GC SI H4 BR	-	IK03	-
910505102866	BY581X 250S/840 SIA HE WB GC SI H4 BR	-	IK03	-
910505102858	BY581X 250S/840 SIA WB GC SI H4	-	IK03	-
910505102859	BY581X 350S/840 SIA WB GC SI H4	-	IK03	-
910505102862	BY581X 250S/840 SIA HE WB GC SI H4	-	IK03	-
910505102863	BY581X 350S/840 SIA HE WB GC SI H4	-	IK03	-
910505102868	BY581X 250S/840 SIA WB GC SI ELP3 H4	-	IK03	-
910505102869	BY581X 250S/840 SIA WB GC SI ELW3 H4	-	IK03	-
910505102870	BY581X 250S/840 SIA HE WB GC SI ELP3 H4	-	IK03	-
910505102871	BY581X 250S/840 SIA HE WB GC SI ELW3 H4	-	IK03	-
910505102864	BY580X 170S/840 SIA WB GC SI H4 BR	-	IK03	-
910505102867	BY580X 170S/840 SIA HE WB GC SI H4 BR	-	IK03	-
910505104565	BY581P 250S/840 DIA HEWBGCSICHEMMBW1mCW5	-	IK07	-
910505102872	BY580P 170S/840 PSU WB GC SI	-	IK07	-
910505102874	BY580P 170S/840 PSU HE WB GC SI	-	IK07	-
910505102876	BY580P 100S/840 DIA UE WB GC SI	-	IK07	-
910505102878	BY580P 130S/840 DIA WB GC SI	-	IK07	-
910505102879	BY580P 170S/840 DIA WB GC SI	-	IK07	-
910505102882	BY580P 130S/840 DIA HE WB GC SI	-	IK07	-
910505102883	BY580P 170S/840 DIA HE WB GC SI	-	IK07	-
910505102886	BY580P 170S/840 DIA WB PC SI	-	IK07	-
910505102890	BY580P 170S/840 DIA HE WB PC SI	-	IK07	-
910505102894	BY580P 170S/840 DIA WB GC SI ELP3	-	IK07	-

Order Code	Full Product Name	Explosion hazard class	Mech. impact protection code	Impact resistance for specific applications
910505102896	BY580P 170S/840 DIA HE WB GC SI ELP3	-	IK07	-
910505102898	BY580P 130S/840 DIA MB GC SI	-	IK07	-
910505102899	BY580P 170S/840 DIA MB GC SI	-	IK07	-
910505102903	BY580P 130S/840 DIA HE MB GC SI	-	IK07	-
910505102904	BY580P 170S/840 DIA HE MB GC SI	-	IK07	-
910505102914	BY580P 170S/840 DIA NB GC SI	-	IK07	-
910505102916	BY580P 170S/840 DIA HE NB GC SI	-	IK07	-
910505102918	BY580P 170S/840 DIA XNB GC SI	-	IK07	-
910505102920	BY580P 170S/840 DIA HE XNB GC SI	-	IK07	-
910505102922	BY580P 170S/840 DIA HRO GC SI	-	IK07	-
910505102924	BY580P 170S/840 DIA HE HRO GC SI	-	IK07	-
910505102926	BY580P 170S/865 DIA WB GC SI	-	IK07	-
910505102928	BY580P 170S/865 DIA HE WB GC SI	-	IK07	-
910505102930	BY580P 170S/830 DIA WB GC SI	-	IK07	-
910505102932	BY580P 170S/830 DIA HE WB GC SI	-	IK07	-
910505102934	BY580P 170S/940 DIA WB GC SI	-	IK07	-
910505104540	BY582P 170S/840 DIA HE WB GC SI 0.5m CW5	Zone 2 and 22	IK07	-
910505104542	BY582P 170S/840 DIA HE WB GC SI 1m CW5	Zone 2 and 22	IK07	-
910505104554	BY580P 170S/840 DIA WB GC SI BP 1m CW5	-	IK07	Ball-proof/ ball-impact resistant lighting
910505104556	BY580P 170S/840 DIA HE WB GC SI BP 1mCW5	-	IK07	Ball-proof/ ball-impact resistant lighting
910505104558	BY580X 170S/840 SIA WB GC SI IA9	-	IK03	-
910505104560	BY580X 170S/840 SIA HE WB GC SI ELP3 IA9	-	IK03	-
910505102910	BY580P 170S/840 DIA ASYM GC SI MBW	-	IK07	-
910505102912	BY580P 170S/840 DIA HE ASYM GC SI MBW	-	IK07	-
910505102889	BY581P 250S/840 DIA WB GC SI BR	-	IK07	-

Order Code	Full Product Name	Explosion hazard class	Mech. impact protection code	Impact resistance for specific applications
910505102893	BY581P 250S/840 DIA HE WB GC SI BR	-	IK07	-
910505102907	BY581P 250S/840 DIA ASYM GC SI BR	-	IK07	-
910505102909	BY581P 250S/840 DIA HE ASYM GC SI BR	-	IK07	-
910505102911	BY581P 250S/840 DIA ASYM GC SI MBW	-	IK07	-
910505102913	BY581P 250S/840 DIA HE ASYM GC SI MBW	-	IK07	-
910505102938	BY581P 350S/840 DIA HE WB GC SI BR XT 1m	-	IK07	-
910505104545	BY581P 250S/840 DIA WB GC SI SWP BR	-	IK07	-
910505104547	BY581P 250S/840 DIA HE WB GC SI SWP BR	-	IK07	-
910505104551	BY581P 250S/840 DIA HE WB GC SI MSP BR	-	IK07	-
910505104553	BY581P 250S/840 PSD WB GC II SI BR	-	IK07	-
910505104559	BY581X 250S/840 SIA WB GC SI IA9	-	IK03	-
910505104561	BY581X 250S/840 SIA HE WB GC SI ELP3 IA9	-	IK03	-
910505104563	BY581P 250S/840 DIA HE WBGCSICHEMBR1mCW5	-	IK07	-
910505102888	BY580P 170S/840 DIA WB GC SI BR	-	IK07	-
910505102892	BY580P 170S/840 DIA HE WB GC SI BR	-	IK07	-
910505102908	BY580P 170S/840 DIA HE ASYM GC SI BR	-	IK07	-
910505104544	BY580P 170S/840 DIA WB GC SI SWP BR	-	IK07	-
910505104546	BY580P 170S/840 DIA HE WB GC SI SWP BR	-	IK07	-
910505104550	BY580P 170S/840 DIA HE WB GC SI MSP BR	-	IK07	-
910505104562	BY580P 170S/840 DIA HE WBGCSICHEMBR1mCW5	-	IK07	-
910505104564	BY580P 170S/840 DIA HEWBGCSICHEMMBW1mCW5	-	IK07	-
910505102873	BY581P 250S/840 PSU WB GC SI	-	IK07	-
910505102875	BY581P 250S/840 PSU HE WB GC SI	-	IK07	-
910505102877	BY581P 200S/840 DIA UE WB GC SI	-	IK07	-
910505102880	BY581P 250S/840 DIA WB GC SI	-	IK07	-
910505102881	BY581P 350S/840 DIA WB GC SI	-	IK07	-
910505102884	BY581P 250S/840 DIA HE WB GC SI	-	IK07	-
910505102885	BY581P 350S/840 DIA HE WB GC SI	-	IK07	-
910505102887	BY581P 250S/840 DIA WB PC SI	-	IK07	-
910505102891	BY581P 250S/840 DIA HE WB PC SI	-	IK07	-
910505102895	BY581P 250S/840 DIA WB GC SI ELD3	-	IK07	-
910505102897	BY581P 250S/840 DIA HE WB GC SI ELD3	-	IK07	-
910505102901	BY581P 250S/840 DIA MB GC SI	-	IK07	-
910505102902	BY581P 350S/840 DIA MB GC SI	-	IK07	-
910505102905	BY581P 250S/840 DIA HE MB GC SI	-	IK07	-
910505102906	BY581P 350S/840 DIA HE MB GC SI	-	IK07	-
910505102915	BY581P 250S/840 DIA NB GC SI	-	IK07	-
910505102917	BY581P 250S/840 DIA HE NB GC SI	-	IK07	-
910505102919	BY581P 250S/840 DIA XNB GC SI	-	IK07	-
910505102921	BY581P 250S/840 DIA HE XNB GC SI	-	IK07	-
910505102923	BY581P 250S/840 DIA HRO GC SI	-	IK07	-
910505102925	BY581P 250S/840 DIA HE HRO GC SI	-	IK07	-
910505102927	BY581P 250S/865 DIA WB GC SI	-	IK07	-
910505102929	BY581P 250S/865 DIA HE WB GC SI	-	IK07	-
910505102931	BY581P 250S/830 DIA WB GC SI	-	IK07	-
910505102933	BY581P 250S/830 DIA HE WB GC SI	-	IK07	-
910505102935	BY581P 250S/940 DIA WB GC SI	-	IK07	-
910505102936	BY581P 250S/840 DIA HE WB GC SI XT 1m	-	IK07	-
910505102937	BY581P 350S/840 DIA HE WB GC SI XT 1m	-	IK07	-
910505104541	BY583P 250S/840 DIA HE WB GC SI 0.5m CW5	Zone 2 and 22	IK07	-
910505104543	BY583P 250S/840 DIA HE WB GC SI 1m CW5	Zone 2 and 22	IK07	-
910505104552	BY581P 250S/840 PSD WB GC II SI	-	IK07	-
910505104555	BY581P 250S/840 DIA WB GC SI BP 1m CW5	-	IK07	Ball-proof/ ball-impact resistant lighting

Order Code	Full Product Name	Explosion hazard class	Mech. impact protection code	Impact resistance for specific applications
910505104557	BY581P 250S/840 DIA HE WB GC SI BP 1mCW5	-	IK07	Ball-proof/ ball-impact resistant lighting
910505102856	BY580X 130S/840 SIA WB GC SI H4	-	IK03	-
910505102857	BY580X 170S/840 SIA WB GC SI H4	-	IK03	-
910505102860	BY580X 130S/840 SIA HE WB GC SI H4	-	IK03	-
910505102861	BY580X 170S/840 SIA HE WB GC SI H4	-	IK03	-

Emergency Operation (1/2)

Order Code	Full Product Name	Emergency lighting	Emergency flux	Type of emergency lighting battery	Power consu during Centra emerg mode
910505102953	BY581P 700S/840 DIA WB GC SI	-	-	-	-
910505102954	BY581P 700S/840 DIA HE WB GC SI	-	-	-	-
910505102955	BY581P 700S/840 DIA WB GC SI BR	-	-	-	-
910505102956	BY581P 700S/840 DIA HE WB GC SI BR	-	-	-	-
910505102865	BY581X 250S/840 SIA WB GC SI H4 BR	-	-	-	-
910505102866	BY581X 250S/840 SIA HE WB GC SI H4 BR	-	-	-	-
910505102858	BY581X 250S/840 SIA WB GC SI H4	-	-	-	-
910505102859	BY581X 350S/840 SIA WB GC SI H4	-	-	-	-
910505102862	BY581X 250S/840 SIA HE WB GC SI H4	-	-	-	-
910505102863	BY581X 350S/840 SIA HE WB GC SI H4	-	-	-	-
910505102868	BY581X 250S/840 SIA WB GC SI ELP3 H4	Emergency lighting 3 hours duration Pro version	850 lm	Lithium	5 W
910505102869	BY581X 250S/840 SIA WB GC SI ELW3 H4	Emergency lighting 3 hours duration with Wireless Interface	850 lm	Lithium	5 W
910505102870	BY581X 250S/840 SIA HE WB GC SI ELP3 H4	Emergency lighting 3	850 lm	Lithium	5 W
910505102871	BY581X 250S/840 SIA HE WB GC SI ELW3 H4	Emergency lighting 3 hours duration with Wireless Interface	850 lm	Lithium	5 W
910505102864	BY580X 170S/840 SIA WB GC SI H4 BR	-	-	-	-
910505102867	BY580X 170S/840 SIA HE WB GC SI H4 BR	-	-	-	-
910505104565	BY581P 250S/840 DIA HEWBGCSICHEMMBW1mCW5	-	-	-	-
910505102872	BY580P 170S/840 PSU WB GC SI	-	-	-	-
910505102874	BY580P 170S/840 PSU HE WB GC SI	-	-	-	-
910505102876	BY580P 100S/840 DIA UE WB GC SI	-	-	-	-
910505102878	BY580P 130S/840 DIA WB GC SI	-	-	-	-
910505102879	BY580P 170S/840 DIA WB GC SI	-	-	-	-
910505102882	BY580P 130S/840 DIA HE WB GC SI	-	-	-	-
910505102883	BY580P 170S/840 DIA HE WB GC SI	-	-	-	-
910505102886	BY580P 170S/840 DIA WB PC SI	-	-	-	-
910505102890	BY580P 170S/840 DIA HE WB PC SI	-	-	-	-

Order Code	Full Product Name	Emergency lighting	Emergency flux	Type of emergency lighting battery	Power consu during Centra emerg mode
910505102894	BY580P 170S/840 DIA WB GC SI ELP3	Emergency lighting 3 hours duration Pro version	450 lm	Lithium	3 W
910505102896	BY580P 170S/840 DIA HE WB GC SI ELP3	Emergency lighting 3 hours duration Pro version	450 lm	Lithium	3 W
910505102898	BY580P 130S/840 DIA MB GC SI	-	-	-	-
910505102899	BY580P 170S/840 DIA MB GC SI	-	-	-	-
910505102903	BY580P 130S/840 DIA HE MB GC SI	-	-	-	-
910505102904	BY580P 170S/840 DIA HE MB GC SI	-	-	-	-
910505102914	BY580P 170S/840 DIA NB GC SI	-	-	-	-
910505102916	BY580P 170S/840 DIA HE NB GC SI	-	-	-	-
910505102918	BY580P 170S/840 DIA XNB GC SI	-	-	-	-
910505102920	BY580P 170S/840 DIA HE XNB GC SI	-	-	-	-
910505102922	BY580P 170S/840 DIA HRO GC SI	-	-	-	-
910505102924	BY580P 170S/840 DIA HE HRO GC SI	-	-	-	-
910505102926	BY580P 170S/865 DIA WB GC SI	-	-	-	-
910505102928	BY580P 170S/865 DIA HE WB GC SI	-	-	-	-
910505102930	BY580P 170S/830 DIA WB GC SI	-	-	-	-
910505102932	BY580P 170S/830 DIA HE WB GC SI	-	-	-	-
910505102934	BY580P 170S/940 DIA WB GC SI	-	-	-	-
910505104540	BY582P 170S/840 DIA HE WB GC SI 0.5m CW5	-	-	-	-
910505104542	BY582P 170S/840 DIA HE WB GC SI 1m CW5	-	-	-	-
910505104554	BY580P 170S/840 DIA WB GC SI BP 1m CW5	-	-	-	-
910505104556	BY580P 170S/840 DIA HE WB GC SI BP 1mCW5	-	-	-	-
910505104558	BY580X 170S/840 SIA WB GC SI IA9	-	-	-	-
910505104560	BY580X 170S/840 SIA HE WB GC SI ELP3 IA9	-	-	-	-
910505102910	BY580P 170S/840 DIA ASYM GC SI MBW	-	-	-	-
910505102912	BY580P 170S/840 DIA HE ASYM GC SI MBW	-	-	-	-
910505102889	BY581P 250S/840 DIA WB GC SI BR	-	-	-	-
910505102893	BY581P 250S/840 DIA HE WB GC SI BR	-	-	-	-
910505102907	BY581P 250S/840 DIA ASYM GC SI BR	-	-	-	-
910505102909	BY581P 250S/840 DIA HE ASYM GC SI BR	-	-	-	-
910505102911	BY581P 250S/840 DIA ASYM GC SI MBW	-	-	-	-
910505102913	BY581P 250S/840 DIA HE ASYM GC SI MBW	-	-	-	-
910505102938	BY581P 350S/840 DIA HE WB GC SI BR XT 1m	-	-	-	-
910505104545	BY581P 250S/840 DIA WB GC SI SWP BR	-	-	-	-
910505104547	BY581P 250S/840 DIA HE WB GC SI SWP BR	-	-	-	-
910505104551	BY581P 250S/840 DIA HE WB GC SI MSP BR	-	-	-	-
910505104553	BY581P 250S/840 PSD WB GC II SI BR	-	-	-	-
910505104559	BY581X 250S/840 SIA WB GC SI IA9	-	-	-	-
910505104561	BY581X 250S/840 SIA HE WB GC SI ELP3 IA9	-	-	-	-
910505104563	BY581P 250S/840 DIA HE WBGCSICHEMBR1mCW5	-	-	-	-
910505102888	BY580P 170S/840 DIA WB GC SI BR	-	-	-	-
910505102892	BY580P 170S/840 DIA HE WB GC SI BR	-	-	-	-
910505102908	BY580P 170S/840 DIA HE ASYM GC SI BR	-	-	-	-
910505104544	BY580P 170S/840 DIA WB GC SI SWP BR	-	-	-	-

Order Code	Full Product Name	Emergency lighting	Emergency flux	Type of emergency lighting battery	Power consumption during Central DC emergency mode
910505104556	BY580P 170S/840 DIA HE WB GC SI BP 1mCW5	-	-	-	-
910505104558	BY580X 170S/840 SIA WB GC SI IA9	-	-	-	-
910505104560	BY580X 170S/840 SIA HE WB GC SI ELP3 IA9	-	-	-	-
910505102910	BY580P 170S/840 DIA ASYM GC SI MBW	-	-	-	-
910505102912	BY580P 170S/840 DIA HE ASYM GC SI MBW	-	-	-	-
910505102889	BY581P 250S/840 DIA WB GC SI BR	-	-	-	-
910505102893	BY581P 250S/840 DIA HE WB GC SI BR	-	-	-	-
910505102907	BY581P 250S/840 DIA ASYM GC SI BR	-	-	-	-
910505102909	BY581P 250S/840 DIA HE ASYM GC SI BR	-	-	-	-
910505102911	BY581P 250S/840 DIA ASYM GC SI MBW	-	-	-	-
910505102913	BY581P 250S/840 DIA HE ASYM GC SI MBW	-	-	-	-
910505102938	BY581P 350S/840 DIA HE WB GC SI BR XT 1m	-	-	-	-
910505104545	BY581P 250S/840 DIA WB GC SI SWP BR	-	-	-	-
910505104547	BY581P 250S/840 DIA HE WB GC SI SWP BR	-	-	-	-
910505104551	BY581P 250S/840 DIA HE WB GC SI MSP BR	-	-	-	-
910505104553	BY581P 250S/840 PSD WB GC II SI BR	-	-	-	-
910505104559	BY581X 250S/840 SIA WB GC SI IA9	-	-	-	-
910505104561	BY581X 250S/840 SIA HE WB GC SI ELP3 IA9	-	-	-	-
910505104563	BY581P 250S/840 DIA HE WBGCSICHEMBR1mCW5	-	-	-	-
910505102888	BY580P 170S/840 DIA WB GC SI BR	-	-	-	-
910505102892	BY580P 170S/840 DIA HE WB GC SI BR	-	-	-	-
910505102908	BY580P 170S/840 DIA HE ASYM GC SI BR	-	-	-	-
910505104544	BY580P 170S/840 DIA WB GC SI SWP BR	-	-	-	-

Order Code	Full Product Name	Emergency lighting	Emergency flux	Type of emergency lighting battery	Power consu during Centra emerg mode
910505104546	BY580P 170S/840 DIA HE WB GC SI SWP BR	-	-	-	-
910505104550	BY580P 170S/840 DIA HE WB GC SI MSP BR	-	-	-	-
910505104562	BY580P 170S/840 DIA HE WBGCSICHEMBR1mCW5	-	-	-	-
910505104564	BY580P 170S/840 DIA HEWBGCSICHEMMBW1mCW5	-	-	-	-
910505102873	BY581P 250S/840 PSU WB GC SI	-	-	-	-
910505102875	BY581P 250S/840 PSU HE WB GC SI	-	-	-	-
910505102877	BY581P 200S/840 DIA UE WB GC SI	-	-	-	-
910505102880	BY581P 250S/840 DIA WB GC SI	-	-	-	-
910505102881	BY581P 350S/840 DIA WB GC SI	-	-	-	-
910505102884	BY581P 250S/840 DIA HE WB GC SI	-	-	-	-
910505102885	BY581P 350S/840 DIA HE WB GC SI	-	-	-	-
910505102887	BY581P 250S/840 DIA WB PC SI	-	-	-	-
910505102891	BY581P 250S/840 DIA HE WB PC SI	-	-	-	-
910505102895	BY581P 250S/840 DIA WB GC SI ELD3	Emergency lighting 3 hours duration with DALI interface	850 lm	Lithium	5 W
910505102897	BY581P 250S/840 DIA HE WB GC SI ELD3	Emergency lighting 3 hours duration with DALI interface	850 lm	Lithium	5 W
910505102901	BY581P 250S/840 DIA MB GC SI	-	-	-	-
910505102902	BY581P 350S/840 DIA MB GC SI	-	-	-	-
910505102905	BY581P 250S/840 DIA HE MB GC SI	-	-	-	-
910505102906	BY581P 350S/840 DIA HE MB GC SI	-	-	-	-

Order Code	Full Product Name	Emergency lighting	Emergency flux	Type of emergency lighting battery	Power consumption during Central DC emergency mode
910505102915	BY581P 250S/840 DIA NB GC SI	-	-	-	-
910505102917	BY581P 250S/840 DIA HE NB GC SI	-	-	-	-
910505102919	BY581P 250S/840 DIA XNB GC SI	-	-	-	-
910505102921	BY581P 250S/840 DIA HE XNB GC SI	-	-	-	-
910505102923	BY581P 250S/840 DIA HRO GC SI	-	-	-	-
910505102925	BY581P 250S/840 DIA HE HRO GC SI	-	-	-	-
910505102927	BY581P 250S/865 DIA WB GC SI	-	-	-	-
910505102929	BY581P 250S/865 DIA HE WB GC SI	-	-	-	-
910505102931	BY581P 250S/830 DIA WB GC SI	-	-	-	-
910505102933	BY581P 250S/830 DIA HE WB GC SI	-	-	-	-
910505102935	BY581P 250S/940 DIA WB GC SI	-	-	-	-
910505102936	BY581P 250S/840 DIA HE WB GC SI XT 1m	-	-	-	-
910505102937	BY581P 350S/840 DIA HE WB GC SI XT 1m	-	-	-	-
910505104541	BY583P 250S/840 DIA HE WB GC SI 0.5m CW5	-	-	-	-
910505104543	BY583P 250S/840 DIA HE WB GC SI 1m CW5	-	-	-	-
910505104552	BY581P 250S/840 PSD WB GC II SI	-	-	-	-
910505104555	BY581P 250S/840 DIA WB GC SI BP 1m CW5	-	-	-	-
910505104557	BY581P 250S/840 DIA HE WB GC SI BP 1mCW5	-	-	-	-
910505102856	BY580X 130S/840 SIA WB GC SI H4	-	-	-	-
910505102857	BY580X 170S/840 SIA WB GC SI H4	-	-	-	-
910505102860	BY580X 130S/840 SIA HE WB GC SI H4	-	-	-	-
910505102861	BY580X 170S/840 SIA HE WB GC SI H4	-	-	-	-

Emergency Operation (2/2)

Order Code	Full Product Name	Rated duration of the emergency lighting (when fully charged)
910505102953	BY581P 700S/840 DIA WB GC SI	-
910505102954	BY581P 700S/840 DIA HE WB GC SI	-
910505102955	BY581P 700S/840 DIA WB GC SI BR	-
910505102956	BY581P 700S/840 DIA HE WB GC SI BR	-
910505102865	BY581X 250S/840 SIA WB GC SI H4 BR	-
910505102866	BY581X 250S/840 SIA HE WB GC SI H4 BR	-
910505102858	BY581X 250S/840 SIA WB GC SI H4	-
910505102859	BY581X 350S/840 SIA WB GC SI H4	-
910505102862	BY581X 250S/840 SIA HE WB GC SI H4	-
910505102863	BY581X 350S/840 SIA HE WB GC SI H4	-
910505102868	BY581X 250S/840 SIA WB GC SI ELP3 H4	3 hour(s)
910505102869	BY581X 250S/840 SIA WB GC SI ELW3 H4	3 hour(s)
910505102870	BY581X 250S/840 SIA HE WB GC SI ELP3 H4	3 hour(s)
910505102871	BY581X 250S/840 SIA HE WB GC SI ELW3 H4	3 hour(s)
910505102864	BY580X 170S/840 SIA WB GC SI H4 BR	-
910505102867	BY580X 170S/840 SIA HE WB GC SI H4 BR	-
910505104565	BY581P 250S/840 DIA HEWBGCSICHEMMBW1mCW5	-
910505102872	BY580P 170S/840 PSU WB GC SI	-
910505102874	BY580P 170S/840 PSU HE WB GC SI	-
910505102876	BY580P 100S/840 DIA UE WB GC SI	-
910505102878	BY580P 130S/840 DIA WB GC SI	-
910505102879	BY580P 170S/840 DIA WB GC SI	-
910505102882	BY580P 130S/840 DIA HE WB GC SI	-
910505102883	BY580P 170S/840 DIA HE WB GC SI	-
910505102886	BY580P 170S/840 DIA WB PC SI	-
910505102890	BY580P 170S/840 DIA HE WB PC SI	-
910505102894	BY580P 170S/840 DIA WB GC SI ELP3	3 hour(s)
910505102896	BY580P 170S/840 DIA HE WB GC SI ELP3	3 hour(s)
910505102898	BY580P 130S/840 DIA MB GC SI	-
910505102899	BY580P 170S/840 DIA MB GC SI	-
910505102903	BY580P 130S/840 DIA HE MB GC SI	-
910505102904	BY580P 170S/840 DIA HE MB GC SI	-
910505102914	BY580P 170S/840 DIA NB GC SI	-
910505102916	BY580P 170S/840 DIA HE NB GC SI	-
910505102918	BY580P 170S/840 DIA XNB GC SI	-
910505102920	BY580P 170S/840 DIA HE XNB GC SI	-
910505102922	BY580P 170S/840 DIA HRO GC SI	-
910505102924	BY580P 170S/840 DIA HE HRO GC SI	-
910505102926	BY580P 170S/865 DIA WB GC SI	-
910505102928	BY580P 170S/865 DIA HE WB GC SI	-
910505102930	BY580P 170S/830 DIA WB GC SI	-
910505102932	BY580P 170S/830 DIA HE WB GC SI	-
910505102934	BY580P 170S/940 DIA WB GC SI	-
910505104540	BY582P 170S/840 DIA HE WB GC SI 0.5m CW5	-
910505104542	BY582P 170S/840 DIA HE WB GC SI 1m CW5	-
910505104554	BY580P 170S/840 DIA WB GC SI BP 1m CW5	-
910505104556	BY580P 170S/840 DIA HE WB GC SI BP 1mCW5	-
910505104558	BY580X 170S/840 SIA WB GC SI IA9	-

Order Code	Full Product Name	Rated duration of the emergency lighting (when fully charged)
910505104560	BY580X 170S/840 SIA HE WB GC SI ELP3 IA9	-
910505102910	BY580P 170S/840 DIA ASYM GC SI MBW	-
910505102912	BY580P 170S/840 DIA HE ASYM GC SI MBW	-
910505102889	BY581P 250S/840 DIA WB GC SI BR	-
910505102893	BY581P 250S/840 DIA HE WB GC SI BR	-
910505102907	BY581P 250S/840 DIA ASYM GC SI BR	-
910505102909	BY581P 250S/840 DIA HE ASYM GC SI BR	-
910505102911	BY581P 250S/840 DIA ASYM GC SI MBW	-
910505102913	BY581P 250S/840 DIA HE ASYM GC SI MBW	-
910505102938	BY581P 350S/840 DIA HE WB GC SI BR XT 1m	-
910505104545	BY581P 250S/840 DIA WB GC SI SWP BR	-
910505104547	BY581P 250S/840 DIA HE WB GC SI SWP BR	-
910505104551	BY581P 250S/840 DIA HE WB GC SI MSP BR	-
910505104553	BY581P 250S/840 PSD WB GC II SI BR	-
910505104559	BY581X 250S/840 SIA WB GC SI IA9	-
910505104561	BY581X 250S/840 SIA HE WB GC SI ELP3 IA9	-
910505104563	BY581P 250S/840 DIA HE WBGCSICHEMBR1mCW5	-
910505102888	BY580P 170S/840 DIA WB GC SI BR	-
910505102892	BY580P 170S/840 DIA HE WB GC SI BR	-
910505102908	BY580P 170S/840 DIA HE ASYM GC SI BR	-
910505104544	BY580P 170S/840 DIA WB GC SI SWP BR	-
910505104546	BY580P 170S/840 DIA HE WB GC SI SWP BR	-
910505104550	BY580P 170S/840 DIA HE WB GC SI MSP BR	-
910505104562	BY580P 170S/840 DIA HE WBGCSICHEMBR1mCW5	-
910505104564	BY580P 170S/840 DIA HEWBGCSICHEMMBW1mCW5	-
910505102873	BY581P 250S/840 PSU WB GC SI	-
910505102875	BY581P 250S/840 PSU HE WB GC SI	-
910505102877	BY581P 200S/840 DIA UE WB GC SI	-
910505102880	BY581P 250S/840 DIA WB GC SI	-
910505102881	BY581P 350S/840 DIA WB GC SI	-
910505102884	BY581P 250S/840 DIA HE WB GC SI	-
910505102885	BY581P 350S/840 DIA HE WB GC SI	-
910505102887	BY581P 250S/840 DIA WB PC SI	-
910505102891	BY581P 250S/840 DIA HE WB PC SI	-
910505102895	BY581P 250S/840 DIA WB GC SI ELD3	3 hour(s)
910505102897	BY581P 250S/840 DIA HE WB GC SI ELD3	3 hour(s)
910505102901	BY581P 250S/840 DIA MB GC SI	-
910505102902	BY581P 350S/840 DIA MB GC SI	-
910505102905	BY581P 250S/840 DIA HE MB GC SI	-
910505102906	BY581P 350S/840 DIA HE MB GC SI	-
910505102915	BY581P 250S/840 DIA NB GC SI	-
910505102917	BY581P 250S/840 DIA HE NB GC SI	-
910505102919	BY581P 250S/840 DIA XNB GC SI	-
910505102921	BY581P 250S/840 DIA HE XNB GC SI	-
910505102923	BY581P 250S/840 DIA HRO GC SI	-
910505102925	BY581P 250S/840 DIA HE HRO GC SI	-
910505102927	BY581P 250S/865 DIA WB GC SI	-
910505102929	BY581P 250S/865 DIA HE WB GC SI	-

Order Code	Full Product Name	Rated duration of the emergency lighting (when fully charged)
910505102931	BY581P 250S/830 DIA WB GC SI	-
910505102933	BY581P 250S/830 DIA HE WB GC SI	-
910505102935	BY581P 250S/940 DIA WB GC SI	-
910505102936	BY581P 250S/840 DIA HE WB GC SI XT 1m	-
910505102937	BY581P 350S/840 DIA HE WB GC SI XT 1m	-
910505104541	BY583P 250S/840 DIA HE WB GC SI 0.5m CW5	-
910505104543	BY583P 250S/840 DIA HE WB GC SI 1m CW5	-

Order Code	Full Product Name	Rated duration of the emergency lighting (when fully charged)
910505104552	BY581P 250S/840 PSD WB GC II SI	-
910505104555	BY581P 250S/840 DIA WB GC SI BP 1m CW5	-
910505104557	BY581P 250S/840 DIA HE WB GC SI BP 1mCW5	-
910505102856	BY580X 130S/840 SIA WB GC SI H4	-
910505102857	BY580X 170S/840 SIA WB GC SI H4	-
910505102860	BY580X 130S/840 SIA HE WB GC SI H4	-
910505102861	BY580X 170S/840 SIA HE WB GC SI H4	-

Approval and Application

Order Code	Full Product Name	Ambient temperature range	Glow-wire test	Flickering value (PstLM) - Flickering value as per EN 61000-3-3	Stro effe visi mea (SV
910505102953	BY581P 700S/840 DIA WB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.22	0.01
910505102954	BY581P 700S/840 DIA HE WB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.22	0.01
910505102955	BY581P 700S/840 DIA WB GC SI BR	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.22	0.01
910505102956	BY581P 700S/840 DIA HE WB GC SI BR	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.22	0.01
910505102865	BY581X 250S/840 SIA WB GC SI H4 BR	-30 to +55 °C	Temperature 650 °C, duration 30 s	1	0.4
910505102866	BY581X 250S/840 SIA HE WB GC SI H4 BR	-30 to +55 °C	Temperature 650 °C, duration 30 s	1	0.4
910505102858	BY581X 250S/840 SIA WB GC SI H4	-30 to +55 °C	Temperature 650 °C, duration 30 s	1	0.4
910505102859	BY581X 350S/840 SIA WB GC SI H4	-30 to +55 °C	Temperature 650 °C, duration 30 s	1	0.4
910505102862	BY581X 250S/840 SIA HE WB GC SI H4	-30 to +55 °C	Temperature 650 °C, duration 30 s	1	0.4
910505102863	BY581X 350S/840 SIA HE WB GC SI H4	-30 to +55 °C	Temperature 650 °C, duration 30 s	1	0.4
910505102868	BY581X 250S/840 SIA WB GC SI ELP3 H4	0 °C to 25 °C	Temperature 850 °C, duration 30 s	1	0.4
910505102869	BY581X 250S/840 SIA WB GC SI ELW3 H4	0 °C to 25 °C	Temperature 850 °C, duration 30 s	1	0.4
910505102870	BY581X 250S/840 SIA HE WB GC SI ELP3 H4	0 °C to 25 °C	Temperature 850 °C, duration 30 s	1	0.4
910505102871	BY581X 250S/840 SIA HE WB GC SI ELW3 H4	0 °C to 25 °C	Temperature 850 °C, duration 30 s	1	0.4
910505102864	BY580X 170S/840 SIA WB GC SI H4 BR	-30 to +55 °C	Temperature 650 °C, duration 30 s	1	0.4

Order Code	Full Product Name	Ambient temperature range	Glow-wire test	Flickering value (PstLM) - Flickering value as per EN 61000-3-3	Stro effe visi mea (SV
910505102867	BY580X 170S/840 SIA HE WB GC SI H4 BR	-30 to +55 °C	Temperature 650 °C, duration 30 s	1	0.4
910505104565	BY581P 250S/840 DIA HEWBGCSICHEMMBW1mCW5	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505102872	BY580P 170S/840 PSU WB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.04	0.07
910505102874	BY580P 170S/840 PSU HE WB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.04	0.07
910505102876	BY580P 100S/840 DIA UE WB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	-	-
910505102878	BY580P 130S/840 DIA WB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	-	-
910505102879	BY580P 170S/840 DIA WB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505102882	BY580P 130S/840 DIA HE WB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	-	-
910505102883	BY580P 170S/840 DIA HE WB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	-	-
910505102886	BY580P 170S/840 DIA WB PC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505102890	BY580P 170S/840 DIA HE WB PC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	-	-
910505102894	BY580P 170S/840 DIA WB GC SI ELP3	0 °C to 25 °C	Temperature 850 °C, duration 30 s	0.12	0.07
910505102896	BY580P 170S/840 DIA HE WB GC SI ELP3	0 °C to 25 °C	Temperature 850 °C, duration 30 s	-	-
910505102898	BY580P 130S/840 DIA MB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	-	-
910505102899	BY580P 170S/840 DIA MB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505102903	BY580P 130S/840 DIA HE MB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	-	-
910505102904	BY580P 170S/840 DIA HE MB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	-	-
910505102914	BY580P 170S/840 DIA NB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	-	-
910505102916	BY580P 170S/840 DIA HE NB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	-	-
910505102918	BY580P 170S/840 DIA XNB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505102920	BY580P 170S/840 DIA HE XNB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	-	-
910505102922	BY580P 170S/840 DIA HRO GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505102924	BY580P 170S/840 DIA HE HRO GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	-	-

Order Code	Full Product Name	Ambient temperature range	Glow-wire test	Flickering value (PstLM) - Flickering value as per EN 61000-3-3	Stro effe visi mea (SV
910505102926	BY580P 170S/865 DIA WB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505102928	BY580P 170S/865 DIA HE WB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	-	-
910505102930	BY580P 170S/830 DIA WB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505102932	BY580P 170S/830 DIA HE WB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	-	-
910505102934	BY580P 170S/940 DIA WB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505104540	BY582P 170S/840 DIA HE WB GC SI 0.5m CW5	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505104542	BY582P 170S/840 DIA HE WB GC SI 1m CW5	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505104554	BY580P 170S/840 DIA WB GC SI BP 1m CW5	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505104556	BY580P 170S/840 DIA HE WB GC SI BP 1mCW5	-30 to +55 °C	Temperature 650 °C, duration 30 s	-	-
910505104558	BY580X 170S/840 SIA WB GC SI IA9	-30 to +55 °C	Temperature 650 °C, duration 30 s	1	0.4
910505104560	BY580X 170S/840 SIA HE WB GC SI ELP3 IA9	-30 to +55 °C	Temperature 650 °C, duration 30 s	1	0.4
910505102910	BY580P 170S/840 DIA ASYM GC SI MBW	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505102912	BY580P 170S/840 DIA HE ASYM GC SI MBW	-30 to +55 °C	Temperature 650 °C, duration 30 s	-	-
910505102889	BY581P 250S/840 DIA WB GC SI BR	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505102893	BY581P 250S/840 DIA HE WB GC SI BR	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505102907	BY581P 250S/840 DIA ASYM GC SI BR	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505102909	BY581P 250S/840 DIA HE ASYM GC SI BR	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505102911	BY581P 250S/840 DIA ASYM GC SI MBW	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505102913	BY581P 250S/840 DIA HE ASYM GC SI MBW	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505102938	BY581P 350S/840 DIA HE WB GC SI BR XT 1m	-30 °C to 55 °C	Temperature 650 °C, duration 30 s	0.22	0.01
910505104545	BY581P 250S/840 DIA WB GC SI SWP BR	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505104547	BY581P 250S/840 DIA HE WB GC SI SWP BR	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505104551	BY581P 250S/840 DIA HE WB GC SI MSP BR	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07

Order Code	Full Product Name	Ambient temperature range	Glow-wire test	Flickering value (PstLM) - Flickering value as per EN 61000-3-3	Stro effe visi mea (SV
910505104553	BY581P 250S/840 PSD WB GC II SI BR	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.35	0.07
910505104559	BY581X 250S/840 SIA WB GC SI IA9	-30 to +55 °C	Temperature 650 °C, duration 30 s	1	0.4
910505104561	BY581X 250S/840 SIA HE WB GC SI ELP3 IA9	-30 to +55 °C	Temperature 650 °C, duration 30 s	1	0.4
910505104563	BY581P 250S/840 DIA HE WBGCSICHEMBR1mCW5	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505102888	BY580P 170S/840 DIA WB GC SI BR	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505102892	BY580P 170S/840 DIA HE WB GC SI BR	-30 to +55 °C	Temperature 650 °C, duration 30 s	-	-
910505102908	BY580P 170S/840 DIA HE ASYM GC SI BR	-30 to +55 °C	Temperature 650 °C, duration 30 s	-	-
910505104544	BY580P 170S/840 DIA WB GC SI SWP BR	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505104546	BY580P 170S/840 DIA HE WB GC SI SWP BR	-30 to +55 °C	Temperature 650 °C, duration 30 s	-	-
910505104550	BY580P 170S/840 DIA HE WB GC SI MSP BR	-30 to +55 °C	Temperature 650 °C, duration 30 s	-	-
910505104562	BY580P 170S/840 DIA HE WBGCSICHEMBR1mCW5	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505104564	BY580P 170S/840 DIA HEWBGCSICHEMMBW1mCW5	-30 to +55 °C	Temperature 650 °C, duration 30 s	-	-
910505102873	BY581P 250S/840 PSU WB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.04	0.07
910505102875	BY581P 250S/840 PSU HE WB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.04	0.07
910505102877	BY581P 200S/840 DIA UE WB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505102880	BY581P 250S/840 DIA WB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505102881	BY581P 350S/840 DIA WB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.22	0.01
910505102884	BY581P 250S/840 DIA HE WB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505102885	BY581P 350S/840 DIA HE WB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.22	0.01
910505102887	BY581P 250S/840 DIA WB PC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505102891	BY581P 250S/840 DIA HE WB PC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505102895	BY581P 250S/840 DIA WB GC SI ELD3	0 °C to 25 °C	Temperature 850 °C, duration 30 s	0.12	0.07
910505102897	BY581P 250S/840 DIA HE WB GC SI ELD3	0 °C to 25 °C	Temperature 850 °C, duration 30 s	0.12	0.07

Order Code	Full Product Name	Ambient temperature range	Glow-wire test	Flickering value (PstLM) - Flickering value as per EN 61000-3-3	Stro effe visi mea (SV
910505102901	BY581P 250S/840 DIA MB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505102902	BY581P 350S/840 DIA MB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.22	0.01
910505102905	BY581P 250S/840 DIA HE MB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505102906	BY581P 350S/840 DIA HE MB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.22	0.01
910505102915	BY581P 250S/840 DIA NB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505102917	BY581P 250S/840 DIA HE NB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505102919	BY581P 250S/840 DIA XNB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505102921	BY581P 250S/840 DIA HE XNB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505102923	BY581P 250S/840 DIA HRO GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505102925	BY581P 250S/840 DIA HE HRO GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505102927	BY581P 250S/865 DIA WB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505102929	BY581P 250S/865 DIA HE WB GC SI	-30 to +55 °C	Temperature 650 °C,	0.12	0.07

Order Code	Full Product Name	Ambient temperature range	Glow-wire test	Flickering value (PstLM) - Flickering value as per EN 61000-3-3	Stroboscop effect visibility measure (SVM)
			duration 30 s		
910505102931	BY581P 250S/830 DIA WB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505102933	BY581P 250S/830 DIA HE WB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505102935	BY581P 250S/940 DIA WB GC SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505102936	BY581P 250S/840 DIA HE WB GC SI XT 1m	-30 °C to 65 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505102937	BY581P 350S/840 DIA HE WB GC SI XT 1m	-30 °C to 55 °C	Temperature 650 °C, duration 30 s	0.22	0.01
910505104541	BY583P 250S/840 DIA HE WB GC SI 0.5m CW5	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505104543	BY583P 250S/840 DIA HE WB GC SI 1m CW5	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505104552	BY581P 250S/840 PSD WB GC II SI	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.35	0.07
910505104555	BY581P 250S/840 DIA WB GC SI BP 1m CW5	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505104557	BY581P 250S/840 DIA HE WB GC SI BP 1mCW5	-30 to +55 °C	Temperature 650 °C, duration 30 s	0.12	0.07
910505102856	BY580X 130S/840 SIA WB GC SI H4	-30 to +55 °C	Temperature 650 °C, duration 30 s	1	0.4

Order Code	Full Product Name	Ambient temperature range	Glow-wire test	Flickering value (PstLM) - Flickering value as per EN 61000-3-3	Stro effe visi mea (SV
910505102857	BY580X 170S/840 SIA WB GC SI H4	-30 to +55 °C	Temperature 650 °C, duration 30 s	1	0.4
910505102860	BY580X 130S/840 SIA HE WB GC SI H4	-30 to +55 °C	Temperature 650 °C,	1	0.4

Order Code	Full Product Name	Ambient temperature range	Glow-wire test	Flickering value (PstLM) - Flickering value as per EN 61000-3-3	Stroboscop effect visibility measure (SVM)
			duration 30 s		
910505102861	BY580X 170S/840 SIA HE WB GC SI H4	-30 to +55 °C	Temperature 650 °C, duration 30 s	1	0.4

Initial Performance (IEC Compliant)

Order Code	Full Product Name	Initial chromaticity
910505102953	BY581P 700S/840 DIA WB GC SI	(0.380, 0.375) SDCM 3
910505102954	BY581P 700S/840 DIA HE WB GC SI	(0.383, 0.377) SDCM 3
910505102955	BY581P 700S/840 DIA WB GC SI BR	(0.380, 0.375) SDCM 3
910505102956	BY581P 700S/840 DIA HE WB GC SI BR	(0.383, 0.377) SDCM 3
910505102865	BY581X 250S/840 SIA WB GC SI H4 BR	(0.380, 0.375) SDCM 3
910505102866	BY581X 250S/840 SIA HE WB GC SI H4 BR	(0.383, 0.377) SDCM 3
910505102858	BY581X 250S/840 SIA WB GC SI H4	(0.380, 0.375) SDCM 3
910505102859	BY581X 350S/840 SIA WB GC SI H4	(0.380, 0.375) SDCM 3
910505102862	BY581X 250S/840 SIA HE WB GC SI H4	(0.383, 0.377) SDCM 3
910505102863	BY581X 350S/840 SIA HE WB GC SI H4	(0.383, 0.377) SDCM 3
910505102868	BY581X 250S/840 SIA WB GC SI ELP3 H4	(0.380, 0.375) SDCM 3
910505102869	BY581X 250S/840 SIA WB GC SI ELW3 H4	(0.380, 0.375) SDCM 3
910505102870	BY581X 250S/840 SIA HE WB GC SI ELP3 H4	(0.383, 0.377) SDCM 3
910505102871	BY581X 250S/840 SIA HE WB GC SI ELW3 H4	(0.383, 0.377) SDCM 3
910505102864	BY580X 170S/840 SIA WB GC SI H4 BR	(0.380, 0.375) SDCM 3
910505102867	BY580X 170S/840 SIA HE WB GC SI H4 BR	(0.383, 0.377) SDCM 3
910505104565	BY581P 250S/840 DIA HEWBGCSICHEMMBW1mCW5	(0.383, 0.377) SDCM 3
910505102872	BY580P 170S/840 PSU WB GC SI	(0.380, 0.375) SDCM 3
910505102874	BY580P 170S/840 PSU HE WB GC SI	(0.383, 0.377) SDCM 3
910505102876	BY580P 100S/840 DIA UE WB GC SI	(0.383, 0.377) SDCM 3
910505102878	BY580P 130S/840 DIA WB GC SI	(0.380, 0.375) SDCM 3
910505102879	BY580P 170S/840 DIA WB GC SI	(0.380, 0.375) SDCM 3
910505102882	BY580P 130S/840 DIA HE WB GC SI	(0.383, 0.377) SDCM 3
910505102883	BY580P 170S/840 DIA HE WB GC SI	(0.383, 0.377) SDCM 3
910505102886	BY580P 170S/840 DIA WB PC SI	(0.380, 0.375) SDCM 3
910505102890	BY580P 170S/840 DIA HE WB PC SI	(0.383, 0.377) SDCM 3
910505102894	BY580P 170S/840 DIA WB GC SI ELP3	(0.380, 0.375) SDCM 3
910505102896	BY580P 170S/840 DIA HE WB GC SI ELP3	(0.383, 0.377) SDCM 3
910505102898	BY580P 130S/840 DIA MB GC SI	(0.380, 0.375) SDCM 3
910505102899	BY580P 170S/840 DIA MB GC SI	(0.380, 0.375) SDCM 3
910505102903	BY580P 130S/840 DIA HE MB GC SI	(0.383, 0.377) SDCM 3
910505102904	BY580P 170S/840 DIA HE MB GC SI	(0.383, 0.377) SDCM 3
910505102914	BY580P 170S/840 DIA NB GC SI	(0.380, 0.375) SDCM 3
910505102916	BY580P 170S/840 DIA HE NB GC SI	(0.383, 0.377) SDCM 3
910505102918	BY580P 170S/840 DIA XNB GC SI	(0.380, 0.375) SDCM 3
910505102920	BY580P 170S/840 DIA HE XNB GC SI	(0.383, 0.377) SDCM 3

Order Code	Full Product Name	Initial chromaticity
910505102922	BY580P 170S/840 DIA HRO GC SI	(0.380, 0.375) SDCM 3
910505102924	BY580P 170S/840 DIA HE HRO GC SI	(0.383, 0.377) SDCM 3
910505102926	BY580P 170S/865 DIA WB GC SI	(0.312, 0.327) SDCM 3
910505102928	BY580P 170S/865 DIA HE WB GC SI	(0.312, 0.325) SDCM 3
910505102930	BY580P 170S/830 DIA WB GC SI	(0.432, 0.400) SDCM 3
910505102932	BY580P 170S/830 DIA HE WB GC SI	(0.435, 0.401) SDCM 3
910505102934	BY580P 170S/940 DIA WB GC SI	(0.380, 0.375) SDCM 3
910505104540	BY582P 170S/840 DIA HE WB GC SI 0.5m CW5	(0.380, 0.375) SDCM 3
910505104542	BY582P 170S/840 DIA HE WB GC SI 1m CW5	(0.380, 0.375) SDCM 3
910505104554	BY580P 170S/840 DIA WB GC SI BP 1m CW5	(0.380, 0.375) SDCM 3
910505104556	BY580P 170S/840 DIA HE WB GC SI BP 1mCW5	(0.383, 0.377) SDCM 3
910505104558	BY580X 170S/840 SIA WB GC SI IA9	(0.380, 0.375) SDCM 3
910505104560	BY580X 170S/840 SIA HE WB GC SI ELP3 IA9	(0.383, 0.377) SDCM 3
910505102910	BY580P 170S/840 DIA ASYM GC SI MBW	(0.380, 0.375) SDCM 3
910505102912	BY580P 170S/840 DIA HE ASYM GC SI MBW	(0.383, 0.377) SDCM 3
910505102889	BY581P 250S/840 DIA WB GC SI BR	(0.380, 0.375) SDCM 3
910505102893	BY581P 250S/840 DIA HE WB GC SI BR	(0.383, 0.377) SDCM 3
910505102907	BY581P 250S/840 DIA ASYM GC SI BR	(0.380, 0.375) SDCM 3
910505102909	BY581P 250S/840 DIA HE ASYM GC SI BR	(0.383, 0.377) SDCM 3
910505102911	BY581P 250S/840 DIA ASYM GC SI MBW	(0.380, 0.375) SDCM 3
910505102913	BY581P 250S/840 DIA HE ASYM GC SI MBW	(0.383, 0.377) SDCM 3
910505102938	BY581P 350S/840 DIA HE WB GC SI BR XT 1m	(0.383, 0.377) SDCM 3
910505104545	BY581P 250S/840 DIA WB GC SI SWP BR	(0.383, 0.377) SDCM 3
910505104547	BY581P 250S/840 DIA HE WB GC SI SWP BR	(0.383, 0.377) SDCM 3
910505104551	BY581P 250S/840 DIA HE WB GC SI MSP BR	(0.383, 0.377) SDCM 3
910505104553	BY581P 250S/840 PSD WB GC II SI BR	(0.380, 0.375) SDCM 3
910505104559	BY581X 250S/840 SIA WB GC SI IA9	(0.380, 0.375) SDCM 3

Order Code	Full Product Name	Initial chromaticity
910505104561	BY581X 250S/840 SIA HE WB GC SI ELP3 IA9	(0.383, 0.377) SDCM 3
910505104563	BY581P 250S/840 DIA HE WBGCSICHEMBR1mCW5	(0.383, 0.377) SDCM 3
910505102888	BY580P 170S/840 DIA WB GC SI BR	(0.380, 0.375) SDCM 3
910505102892	BY580P 170S/840 DIA HE WB GC SI BR	(0.383, 0.377) SDCM 3
910505102908	BY580P 170S/840 DIA HE ASYM GC SI BR	(0.383, 0.377) SDCM 3
910505104544	BY580P 170S/840 DIA WB GC SI SWP BR	(0.380, 0.375) SDCM 3
910505104546	BY580P 170S/840 DIA HE WB GC SI SWP BR	(0.383, 0.377) SDCM 3
910505104550	BY580P 170S/840 DIA HE WB GC SI MSP BR	(0.383, 0.377) SDCM 3
910505104562	BY580P 170S/840 DIA HE WBGCSICHEMBR1mCW5	(0.383, 0.377) SDCM 3
910505104564	BY580P 170S/840 DIA HEWBGCSICHEMMBW1mCW5	(0.383, 0.377) SDCM 3
910505102873	BY581P 250S/840 PSU WB GC SI	(0.380, 0.375) SDCM 3
910505102875	BY581P 250S/840 PSU HE WB GC SI	(0.383, 0.377) SDCM 3
910505102877	BY581P 200S/840 DIA UE WB GC SI	(0.383, 0.377) SDCM 3
910505102880	BY581P 250S/840 DIA WB GC SI	(0.380, 0.375) SDCM 3
910505102881	BY581P 350S/840 DIA WB GC SI	(0.380, 0.375) SDCM 3
910505102884	BY581P 250S/840 DIA HE WB GC SI	(0.383, 0.377) SDCM 3
910505102885	BY581P 350S/840 DIA HE WB GC SI	(0.383, 0.377) SDCM 3
910505102887	BY581P 250S/840 DIA WB PC SI	(0.380, 0.375) SDCM 3
910505102891	BY581P 250S/840 DIA HE WB PC SI	(0.383, 0.377) SDCM 3
910505102895	BY581P 250S/840 DIA WB GC SI ELD3	(0.380, 0.375) SDCM 3
910505102897	BY581P 250S/840 DIA HE WB GC SI ELD3	(0.383, 0.377) SDCM 3
910505102901	BY581P 250S/840 DIA MB GC SI	(0.380, 0.375) SDCM 3
910505102902	BY581P 350S/840 DIA MB GC SI	(0.380, 0.375) SDCM 3
910505102905	BY581P 250S/840 DIA HE MB GC SI	(0.383, 0.377) SDCM 3
910505102906	BY581P 350S/840 DIA HE MB GC SI	(0.383, 0.377) SDCM 3
910505102915	BY581P 250S/840 DIA NB GC SI	(0.380, 0.375) SDCM 3

Order Code	Full Product Name	Initial chromaticity
910505102917	BY581P 250S/840 DIA HE NB GC SI	(0.383, 0.377) SDCM 3
910505102919	BY581P 250S/840 DIA XNB GC SI	(0.380, 0.375) SDCM 3
910505102921	BY581P 250S/840 DIA HE XNB GC SI	(0.383, 0.377) SDCM 3
910505102923	BY581P 250S/840 DIA HRO GC SI	(0.380, 0.375) SDCM 3
910505102925	BY581P 250S/840 DIA HE HRO GC SI	(0.383, 0.377) SDCM 3
910505102927	BY581P 250S/865 DIA WB GC SI	(0.312, 0.327) SDCM 3
910505102929	BY581P 250S/865 DIA HE WB GC SI	(0.312, 0.325) SDCM 3
910505102931	BY581P 250S/830 DIA WB GC SI	(0.432, 0.400) SDCM 3
910505102933	BY581P 250S/830 DIA HE WB GC SI	(0.435, 0.401) SDCM 3
910505102935	BY581P 250S/940 DIA WB GC SI	(0.380, 0.375) SDCM 3
910505102936	BY581P 250S/840 DIA HE WB GC SI XT 1m	(0.383, 0.377) SDCM 3

Order Code	Full Product Name	Initial chromaticity
910505102937	BY581P 350S/840 DIA HE WB GC SI XT 1m	(0.383, 0.377) SDCM 3
910505104541	BY583P 250S/840 DIA HE WB GC SI 0.5m CW5	(0.380, 0.375) SDCM 3
910505104543	BY583P 250S/840 DIA HE WB GC SI 1m CW5	(0.380, 0.375) SDCM 3
910505104552	BY581P 250S/840 PSD WB GC II SI	(0.380, 0.375) SDCM 3
910505104555	BY581P 250S/840 DIA WB GC SI BP 1m CW5	(0.380, 0.375) SDCM 3
910505104557	BY581P 250S/840 DIA HE WB GC SI BP 1mCW5	(0.383, 0.377) SDCM 3
910505102856	BY580X 130S/840 SIA WB GC SI H4	(0.380, 0.375) SDCM 3
910505102857	BY580X 170S/840 SIA WB GC SI H4	(0.380, 0.375) SDCM 3
910505102860	BY580X 130S/840 SIA HE WB GC SI H4	(0.383, 0.377) SDCM 3
910505102861	BY580X 170S/840 SIA HE WB GC SI H4	(0.383, 0.377) SDCM 3

Product Data


Order Code	Full Product Name	Product family code
910505102953	BY581P 700S/840 DIA WB GC SI	BY581P
910505102954	BY581P 700S/840 DIA HE WB GC SI	BY581P
910505102955	BY581P 700S/840 DIA WB GC SI BR	BY581P
910505102956	BY581P 700S/840 DIA HE WB GC SI BR	BY581P
910505102865	BY581X 250S/840 SIA WB GC SI H4 BR	BY580X
910505102866	BY581X 250S/840 SIA HE WB GC SI H4 BR	BY581X
910505102858	BY581X 250S/840 SIA WB GC SI H4	BY580X
910505102859	BY581X 350S/840 SIA WB GC SI H4	BY581X
910505102862	BY581X 250S/840 SIA HE WB GC SI H4	BY581X
910505102863	BY581X 350S/840 SIA HE WB GC SI H4	BY581X
910505102868	BY581X 250S/840 SIA WB GC SI ELP3 H4	BY581X
910505102869	BY581X 250S/840 SIA WB GC SI ELW3 H4	BY581X
910505102870	BY581X 250S/840 SIA HE WB GC SI ELP3 H4	BY581X
910505102871	BY581X 250S/840 SIA HE WB GC SI ELW3 H4	BY581X
910505102864	BY580X 170S/840 SIA WB GC SI H4 BR	BY580X
910505102867	BY580X 170S/840 SIA HE WB GC SI H4 BR	BY580X
910505104565	BY581P 250S/840 DIA HEWBGCSICHEMMBW1mCW5	BY581P
910505102872	BY580P 170S/840 PSU WB GC SI	BY580P
910505102874	BY580P 170S/840 PSU HE WB GC SI	BY580P
910505102876	BY580P 100S/840 DIA UE WB GC SI	BY580P
910505102878	BY580P 130S/840 DIA WB GC SI	BY580P
910505102879	BY580P 170S/840 DIA WB GC SI	BY580P
910505102882	BY580P 130S/840 DIA HE WB GC SI	BY580P
910505102883	BY580P 170S/840 DIA HE WB GC SI	BY580P
910505102886	BY580P 170S/840 DIA WB PC SI	BY580P
910505102890	BY580P 170S/840 DIA HE WB PC SI	BY580P
910505102894	BY580P 170S/840 DIA WB GC SI ELP3	BY580P

Order Code	Full Product Name	Product family code
910505102896	BY580P 170S/840 DIA HE WB GC SI ELP3	BY580P
910505102898	BY580P 130S/840 DIA MB GC SI	BY580P
910505102899	BY580P 170S/840 DIA MB GC SI	BY580P
910505102903	BY580P 130S/840 DIA HE MB GC SI	BY580P
910505102904	BY580P 170S/840 DIA HE MB GC SI	BY580P
910505102914	BY580P 170S/840 DIA NB GC SI	BY580P
910505102916	BY580P 170S/840 DIA HE NB GC SI	BY580P
910505102918	BY580P 170S/840 DIA XNB GC SI	BY580P
910505102920	BY580P 170S/840 DIA HE XNB GC SI	BY580P
910505102922	BY580P 170S/840 DIA HRO GC SI	BY580P
910505102924	BY580P 170S/840 DIA HE HRO GC SI	BY580P
910505102926	BY580P 170S/865 DIA WB GC SI	BY580P
910505102928	BY580P 170S/865 DIA HE WB GC SI	BY580P
910505102930	BY580P 170S/830 DIA WB GC SI	BY580P
910505102932	BY580P 170S/830 DIA HE WB GC SI	BY580P
910505102934	BY580P 170S/940 DIA WB GC SI	BY580P
910505104540	BY582P 170S/840 DIA HE WB GC SI 0.5m CW5	BY582P
910505104542	BY582P 170S/840 DIA HE WB GC SI 1m CW5	BY582P
910505104554	BY580P 170S/840 DIA WB GC SI BP 1m CW5	BY580P
910505104556	BY580P 170S/840 DIA HE WB GC SI BP 1mCW5	BY580P
910505104558	BY580X 170S/840 SIA WB GC SI IA9	BY580X
910505104560	BY580X 170S/840 SIA HE WB GC SI ELP3 IA9	BY580X
910505102910	BY580P 170S/840 DIA ASYM GC SI MBW	BY580P
910505102912	BY580P 170S/840 DIA HE ASYM GC SI MBW	BY580P
910505102889	BY581P 250S/840 DIA WB GC SI BR	BY581P
910505102893	BY581P 250S/840 DIA HE WB GC SI BR	BY581P
910505102907	BY581P 250S/840 DIA ASYM GC SI BR	BY581P


Order Code	Full Product Name	Product family code
910505102909	BY581P 250S/840 DIA HE ASYM GC SI BR	BY581P
910505102911	BY581P 250S/840 DIA ASYM GC SI MBW	BY581P
910505102913	BY581P 250S/840 DIA HE ASYM GC SI MBW	BY581P
910505102938	BY581P 350S/840 DIA HE WB GC SI BR XT 1m	BY581P
910505104545	BY581P 250S/840 DIA WB GC SI SWP BR	BY581P
910505104547	BY581P 250S/840 DIA HE WB GC SI SWP BR	BY581P
910505104551	BY581P 250S/840 DIA HE WB GC SI MSP BR	BY581P
910505104553	BY581P 250S/840 PSD WB GC II SI BR	BY581P
910505104559	BY581X 250S/840 SIA WB GC SI IA9	BY581X
910505104561	BY581X 250S/840 SIA HE WB GC SI ELP3 IA9	BY581X
910505104563	BY581P 250S/840 DIA HE WBGCSICHEMBR1mCW5	BY581P
910505102888	BY580P 170S/840 DIA WB GC SI BR	BY580P
910505102892	BY580P 170S/840 DIA HE WB GC SI BR	BY580P
910505102908	BY580P 170S/840 DIA HE ASYM GC SI BR	BY580P
910505104544	BY580P 170S/840 DIA WB GC SI SWP BR	BY580P
910505104546	BY580P 170S/840 DIA HE WB GC SI SWP BR	BY580P
910505104550	BY580P 170S/840 DIA HE WB GC SI MSP BR	BY580P
910505104562	BY580P 170S/840 DIA HE WBGCSICHEMBR1mCW5	BY580P
910505104564	BY580P 170S/840 DIA HEWBGCSICHEMMBW1mCW5	BY580P
910505102873	BY581P 250S/840 PSU WB GC SI	BY581P
910505102875	BY581P 250S/840 PSU HE WB GC SI	BY581P
910505102877	BY581P 200S/840 DIA UE WB GC SI	BY581P
910505102880	BY581P 250S/840 DIA WB GC SI	BY581P
910505102881	BY581P 350S/840 DIA WB GC SI	BY581P
910505102884	BY581P 250S/840 DIA HE WB GC SI	BY581P
910505102885	BY581P 350S/840 DIA HE WB GC SI	BY581P
910505102887	BY581P 250S/840 DIA WB PC SI	BY581P
910505102891	BY581P 250S/840 DIA HE WB PC SI	BY581P

Order Code	Full Product Name	Product family code
910505102895	BY581P 250S/840 DIA WB GC SI ELD3	BY581P
910505102897	BY581P 250S/840 DIA HE WB GC SI ELD3	BY581P
910505102901	BY581P 250S/840 DIA MB GC SI	BY581P
910505102902	BY581P 350S/840 DIA MB GC SI	BY581P
910505102905	BY581P 250S/840 DIA HE MB GC SI	BY581P
910505102906	BY581P 350S/840 DIA HE MB GC SI	BY581P
910505102915	BY581P 250S/840 DIA NB GC SI	BY581P
910505102917	BY581P 250S/840 DIA HE NB GC SI	BY581P
910505102919	BY581P 250S/840 DIA XNB GC SI	BY581P
910505102921	BY581P 250S/840 DIA HE XNB GC SI	BY581P
910505102923	BY581P 250S/840 DIA HRO GC SI	BY581P
910505102925	BY581P 250S/840 DIA HE HRO GC SI	BY581P
910505102927	BY581P 250S/865 DIA WB GC SI	BY581P
910505102929	BY581P 250S/865 DIA HE WB GC SI	BY581P
910505102931	BY581P 250S/830 DIA WB GC SI	BY581P
910505102933	BY581P 250S/830 DIA HE WB GC SI	BY581P
910505102935	BY581P 250S/940 DIA WB GC SI	BY581P
910505102936	BY581P 250S/840 DIA HE WB GC SI XT 1m	BY581P
910505102937	BY581P 350S/840 DIA HE WB GC SI XT 1m	BY581P
910505104541	BY583P 250S/840 DIA HE WB GC SI 0.5m CW5	BY583P
910505104543	BY583P 250S/840 DIA HE WB GC SI 1m CW5	BY583P
910505104552	BY581P 250S/840 PSD WB GC II SI	BY581P
910505104555	BY581P 250S/840 DIA WB GC SI BP 1m CW5	BY581P
910505104557	BY581P 250S/840 DIA HE WB GC SI BP 1mCW5	BY581P
910505102856	BY580X 130S/840 SIA WB GC SI H4	BY580X
910505102857	BY580X 170S/840 SIA WB GC SI H4	BY580X
910505102860	BY580X 130S/840 SIA HE WB GC SI H4	BY580X
910505102861	BY580X 170S/840 SIA HE WB GC SI H4	BY580X


Polar Wide Diagrams



Polar Normal (separate) - BY580PI - 910505104540




Polar Normal (separate) - BY580PI - 910505104542




Polar Normal (separate) - BY580PI - 910505104541


Polar Wide Diagrams




Polar Normal (separate) - BY580PI - 910505104543




Polar Normal (separate) - BY580PI - 910505102872




Polar Normal (separate) - BY580PI - 910505102863




Polar Normal (separate) - BY580PI - 910505102914




Polar Normal (separate) - BY580PI - 910505102899




Polar Normal (separate) - BY580PI - 910505102869



Polar Normal (separate) - BY580PI - 910505102915




Polar Normal (separate) - BY580PI - 910505102865




Polar Normal (separate) - BY580PI - 910505102895


Polar Wide Diagrams




Polar Normal (separate) - BY580PI - 910505102898




Polar Normal (separate) - BY580PI - 910505102856




Polar Normal (separate) - BY580PI - 910505102924




Polar Normal (separate) - BY580PI - 910505102881




Polar Normal (separate) - BY580PI - 910505102925




Polar Normal (separate) - BY580PI - 910505102857



Polar Normal (separate) - BY580PI - 910505102933




Polar Normal (separate) - BY580PI - 910505102873




Polar Normal (separate) - BY580PI - 910505102902


Polar Wide Diagrams




Polar Normal (separate) - BY580PI - 910505102884




Polar Normal (separate) - BY580PI - 910505102874




Polar Normal (separate) - BY580PI - 910505102896




Polar Normal (separate) - BY580PI - 910505102875




Polar Normal (separate) - BY580PI - 910505102868




Polar Normal (separate) - BY580PI - 910505102923



Polar Normal (separate) - BY580PI - 910505102858




Polar Normal (separate) - BY580PI - 910505102871




Polar Normal (separate) - BY580PI - 910505102901


Polar Wide Diagrams




Polar Normal (separate) - BY580PI - 910505102922




Polar Normal (separate) - BY580PI - 910505102862




Polar Normal (separate) - BY580PI - 910505102906




Polar Normal (separate) - BY580PI - 910505102921




Polar Normal (separate) - BY580PI - 910505102920




Polar Normal (separate) - BY580PI - 910505102932



Polar Normal (separate) - BY580PI - 910505102864




Polar Normal (separate) - BY580PI - 910505102934




Polar Normal (separate) - BY580PI - 910505102878


Polar Wide Diagrams




Polar Normal (separate) - BY580PI - 910505102866




Polar Normal (separate) - BY580PI - 910505102885




Polar Normal (separate) - BY580PI - 910505102883




Polar Normal (separate) - BY580PI - 910505102918




Polar Normal (separate) - BY580PI - 910505102882




Polar Normal (separate) - BY580PI - 910505102916



Polar Normal (separate) - BY580PI - 910505102926




Polar Normal (separate) - BY580PI - 910505102928




Polar Normal (separate) - BY580PI - 910505102935


Polar Wide Diagrams




Polar Normal (separate) - BY580PI - 910505102903




Polar Normal (separate) - BY580PI - 910505102891




Polar Normal (separate) - BY580PI - 910505102904




Polar Normal (separate) - BY580PI - 910505102886




Polar Normal (separate) - BY580PI - 910505102867




Polar Normal (separate) - BY580PI - 910505102905



Polar Normal (separate) - BY580PI - 910505102890




Polar Normal (separate) - BY580PI - 910505102894




Polar Normal (separate) - BY580PI - 910505102930


Polar Wide Diagrams




Polar Normal (separate) - BY580PI - 910505102919




Polar Normal (separate) - BY580PI - 910505102879




Polar Normal (separate) - BY580PI - 910505102870




Polar Normal (separate) - BY580PI - 910505102887




Polar Normal (separate) - BY580PI - 910505102859




Polar Normal (separate) - BY580PI - 910505102892



Polar Normal (separate) - BY580PI - 910505102893




Polar Normal (separate) - BY580PI - 910505102860




Polar Normal (separate) - BY580PI - 910505102929


Polar Wide Diagrams




Polar Normal (separate) - BY580PI - 910505102931




Polar Normal (separate) - BY580PI - 910505102917




Polar Normal (separate) - BY580PI - 910505102877




Polar Normal (separate) - BY580PI - 910505102889




Polar Normal (separate) - BY580PI - 910505102927




Polar Normal (separate) - BY580PI - 910505102861



Polar Normal (separate) - BY580PI - 910505102888




Polar Normal (separate) - BY580PI - 910505102880




Polar Normal (separate) - BY580PI - 910505102897


Polar Wide Diagrams




Polar Normal (separate) - BY580PI - 910505102876




Polar Normal (separate) - BY580PI - 910505102938




Polar Normal (separate) - BY580PI - 910505102936




Polar Normal (separate) - BY580PI - 910505102937




Polar Normal (separate) - BY580PI - 910505104547




Polar Normal (separate) - BY580PI - 910505104550



Polar Normal (separate) - BY580PI - 910505104545




Polar Normal (separate) - BY580PI - 910505104544




Polar Normal (separate) - BY580PI - 910505104551


Polar Wide Diagrams




Polar Normal (separate) - BY580PI - 910505104546




Polar Normal (separate) - BY580PI - 910505102907




Polar Normal (separate) - BY580PI - 910505102913




Polar Normal (separate) - BY580PI - 910505102912




Polar Normal (separate) - BY580PI - 910505102909




Polar Normal (separate) - BY580PI - 910505102908



Polar Normal (separate) - BY580PI - 910505102910




Polar Normal (separate) - BY580PI - 910505102911




Polar Normal (separate) - BY580PI - 910505104557


Polar Wide Diagrams




Polar Normal (separate) - BY580PI - 910505104554




Polar Normal (separate) - BY580PI - 910505104555




Polar Normal (separate) - BY580PI - 910505104563




Polar Normal (separate) - BY580PI - 910505104556




Polar Normal (separate) - BY580PI - 910505104564




Polar Normal (separate) - BY580PI - 910505104565



Polar Normal (separate) - BY580PI - 910505104562




Polar Normal (separate) - BY580PI - 910505104561




Polar Normal (separate) - BY580PI - 910505104552

GentleSpace gen4


Polar Wide Diagrams




Polar Normal (separate) - BY580PI - 910505104553



Polar Normal (separate) - BY580PI - 910505104558



Polar Normal (separate) - BY580PI - 910505104559



Polar Normal (separate) - BY580PI - 910505104560

© 2026 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.